



**Federal Aviation
Administration**

Aeronautical Information Services

Aeronautical Chart User's Guide

Effective as of 12 October 2017

Table of Contents

Contents

INTRODUCTION	7
KEEP YOUR CHARTS CURRENT	7
EFFECTIVE DATE OF CHART USERS GUIDE AND UPDATES	7
COLOR VARIATION	7
REPORTING CHART DISCREPANCIES	7
WHAT'S NEW?	9
VFR CHARTS	9
WHAT'S NEW - IFR ENROUTE CHARTS	10
TERMINAL PROCEDURE PUBLICATIONS (TPPS).....	11
EXPLANATION OF VFR TERMS AND SYMBOLS	13
WATER FEATURES (HYDROGRAPHY)	13
LAND FEATURES (TERRAIN) AND OBSTRUCTIONS	13
RADIO AIDS TO NAVIGATION	17
AIRPORTS	17
AIRSPACE.....	19
TERMINAL AREA CHART (TAC) COVERAGE	22
INSET AND SPECIAL CHART COVERAGE	22
CHART TABULATIONS	22
WORLD AERONAUTICAL CHARTS (WAC)	24
CARIBBEAN VFR AERONAUTICAL CHARTS (CAC)	24
VFR SECTIONAL AND TERMINAL AREA CHARTS	25
AIRPORTS	25
RADIO AIDS TO NAVIGATION	27
AIRSPACE INFORMATION.....	28
NAVIGATIONAL AND PROCEDURAL INFORMATION	34
CULTURE	36
HYDROGRAPHY	39
RELIEF	42
VFR FLYWAY PLANNING CHARTS	45
GENERAL INFORMATION.....	45
AIRPORTS	45
RADIO AIDS TO NAVIGATION	45
AIRSPACE INFORMATION.....	46
NAVIGATIONAL AND PROCEDURAL INFORMATION	49
CULTURE	49
BOUNDARIES.....	49
HYDROGRAPHY	50
RELIEF	50

Table of Contents

HELICOPTER ROUTE CHARTS	51
GENERAL INFORMATION.....	51
AIRPORTS	51
RADIO AIDS TO NAVIGATION	52
AIRSPACE INFORMATION.....	53
NAVIGATIONAL AND PROCEDURAL INFORMATION	56
CULTURE.....	57
VFR AIRSPACE CLASSES	59
EXPLANATION OF IFR ENROUTE TERMS	63
AIRPORTS	63
RADIO AIDS TO NAVIGATION	64
AIRSPACE INFORMATION.....	66
INSTRUMENT AIRWAYS	68
TERRAIN CONTOURS ON AREA CHARTS.....	71
AIRPORTS	73
IFR ENROUTE LOW / HIGH ALTITUDE SYMBOLS (U.S., PACIFIC AND ALASKA CHARTS)	73
RADIO AIDS TO NAVIGATION	74
AIRSPACE INFORMATION.....	79
NAVIGATIONAL AND PROCEDURAL INFORMATION	92
CULTURE.....	93
HYDROGRAPHY	93
TOPOGRAPHY	93
U.S. TERMINAL PROCEDURES PUBLICATION	95
EXPLANATION OF TPP TERMS AND SYMBOLS	95
INSTRUMENT APPROACH PROCEDURE CHART.....	96
PLANVIEW	102
NAVAIDS	105
MISSED APPROACH INFORMATION	110
PROFILE VIEW	111
LANDING MINIMUMS.....	114
AIRPORT SKETCH	116
AIRPORT DIAGRAMS	117
DEPARTURE PROCEDURES (DPs).....	119
STANDARD TERMINAL ARRIVAL (STARs) CHARTS	119
CHARTED VISUAL FLIGHT PROCEDURE (CVFP) CHARTS	120

Table of Contents

U.S. TERMINAL PROCEDURES PUBLICATION SYMBOLS	121
GENERAL INFORMATION.....	121
LEGEND - STANDARD TERMINAL ARRIVAL (STAR) CHARTS - DEPARTURE PROCEDURE (DP) CHARTS.....	121
APPROACH LIGHTING SYSTEM.....	122
AIRPORT DIAGRAM/AIRPORT SKETCH	124
PLANVIEW SYMBOLS.....	125
PROFILE VIEW	127
COLD TEMPERATURE AIRPORTS.....	128

REFERENCES.....	129
------------------------	------------

ABBREVIATIONS	131
----------------------------	------------

A.....	131
B.....	131
C.....	131
D.....	131
E.....	131
F.....	131
G.....	131
H.....	131
I.....	131
K.....	132
L.....	132
M.....	132
N.....	132
O.....	132
P.....	132
R.....	132
S.....	132
T.....	133
U.....	133
V.....	133
W.....	133

INTRODUCTION

This Chart User's Guide is an introduction to the Federal Aviation Administration's (FAA) aeronautical charts and publications. It is useful to new pilots as a learning aid, and to experienced pilots as a quick reference guide.

The FAA is the source for all data and information utilized in the publishing of aeronautical charts through authorized publishers for each stage of Visual Flight Rules (VFR) and Instrument Flight Rules (IFR) air navigation including training, planning, and departures, enroute (for low and high altitudes), approaches, and taxiing charts. Digital charts are available online at:

- VFR Charts - https://www.faa.gov/air_traffic/flight_info/aeronav/digital_products/vfr/
- IFR Charts - https://www.faa.gov/air_traffic/flight_info/aeronav/digital_products/ifr/
- Terminal Procedures Publication - http://www.faa.gov/air_traffic/flight_info/aeronav/digital_products/dtpp/
- Chart Supplements - https://www.faa.gov/air_traffic/flight_info/aeronav/digital_products/dafd/

Paper copies of the charts are available through an FAA Approved Print Provider. A complete list of current providers is available at http://www.faa.gov/air_traffic/flight_info/aeronav/print_providers/

The FAA Aeronautical Information Manual (AIM) Pilot/Controller Glossary defines in detail, all terms and abbreviations used throughout this publication. Unless otherwise indicated, miles are nautical miles (NM), altitudes indicate feet above Mean Sea Level (MSL), and times used are Coordinated Universal Time (UTC).

The Notices to Airmen Publication (NOTAM) includes current Flight Data Center (FDC) NOTAMs. NOTAMs alert pilots of new regulatory requirements and reflect changes to Standard Instrument Approach Procedures (SIAPs), flight restrictions, and aeronautical chart revisions. This publication is prepared every 28 days by the FAA, and is available by subscription from the Government Printing Office. For more information on subscribing or to access online PDF copy, http://www.faa.gov/air_traffic/publications/notices/

In addition to NOTAMs, the Chart Supplement and the Safety Alerts/Charting Notices page of the Aeronautical Information Services website are also useful to pilots

KEEP YOUR CHARTS CURRENT

Aeronautical information changes rapidly, so it is important that pilots check the effective dates on each aeronautical chart and publication. To avoid danger, it is important to always use current editions and discard obsolete charts and publications.

To confirm that a chart or publication is current, refer to the next scheduled edition date printed on the cover. Pilots should also check Aeronautical Chart Bulletins and NOTAMs for important updates between chart and publication cycles that are essential for safe flight.

EFFECTIVE DATE OF CHART USERS GUIDE AND UPDATES

All information in this guide is effective as of 12 October 2017. All graphics used in this guide are for educational purposes. Please do not use them for flight navigation. The Chart Users Guide is updated as necessary, i.e. new chart symbology, changes in depiction of information and/or symbols on the charts, etc. Chart symbology may not be to scale.

COLOR VARIATION

Although the digital files are compiled in accordance with the charting specifications, the final product may vary slightly in appearance due to differences in printing techniques/processes and/or digital display techniques.

REPORTING CHART DISCREPANCIES

Your experience as a pilot is valuable and your feedback is important. We make every effort to display accurate information on all FAA charts and publications, so we appreciate your input. Please notify us concerning any requests for changes, or potential discrepancies you see while using our charts and related products.

*FAA, Aeronautical Information Services
Customer Operations Team
1305 East-West Highway
SSMC4 Suite 4400
Silver Spring, MD 20910-3281*

*Telephone Toll-Free 1-800-638-8972
E-mail: 9-AMC-Aerochart@faa.gov*

WHAT'S NEW?

Update as of 12 October 2017

A new feature to the Chart Users Guide is this What's New section which will highlight new charting symbology and other changes to charts.


The following charting items have been added to the Online Chart Users Guide since the Guide was last published in 2011:

VFR CHARTS

NEW Series of VFR Charts

Caribbean VFR Aeronautical Charts 1 and 2 (CAC-1 and CAC-2) are designed for visual navigation to assist familiarization of foreign aeronautical and topographic information. The aeronautical information includes visual and radio aids to navigation, airports, controlled airspace, special-use airspace, obstructions, and related data. The topographic information consists of contour lines, shaded relief, drainage patterns, and a selection of landmarks used for flight under VFR. Cultural features include cities and towns, roads, railroads, and other distinct landmarks. CAC-1 is revised annually and consists of two sides measuring 30" x 60" each. CAC-2 is revised biennially and consists of two sides measuring 20" x 60" each.

Starting in 2016, the FAA CARIBBEAN VFR Aeronautical Charts were first published, replacing the discontinued WACs, parts of CH-25, CJ-26, and CJ-27, with CJ-27's last effective date of 1 February 2018 and CJ-26 last effective date of 29 March 2018. The Caribbean Charts are published as two VFR Charts: Caribbean 1 (CAC-1) chart covering mostly Southern Florida, Cuba, Haiti and the Bahamas; Caribbean 2 (CAC-2) chart, covering Puerto Rico, Haiti, Dominican Republic, the Lesser Antilles and Leeward Islands. CAC-1 is updated annually and CAC-2 biennially.



Example from Caribbean 1 VFR Aeronautical Chart

Starting in 2016, the FAA CARIBBEAN VFR Aeronautical Charts were first published, replacing the discontinued WACs,

NAVAIDs


DME (Stand Alone DME)



WHAT'S NEW - VFR CHARTS (Continued)

AIRSPACE

Special Security Notice
Permanent Continuous
Flight Restriction Areas



Example: Jacksonville Sectional Chart



Example: Tampa-Orlando Terminal Chart



Sporting Event Temporary
Flight Restriction (TFR) Sites



Miscellaneous Airspace:
Special Activity Areas:
Aerobatic Practice Areas



Miscellaneous Airspace:
Special Activity Areas:
Space Launch Activity Areas



CHART LIMITS

Outline of Special Chart
on Sectional and Terminal
Area Chart



WHAT'S NEW - IFR ENROUTE CHARTS

NAVAIDS

DME (Stand Alone DME)



AIRSPACE INFORMATION

Minimum Turning Altitude (MTA)



WHAT'S NEW (Continued)

TERMINAL PROCEDURE PUBLICATIONS (TPPS)

NAVAIDs

DME (Stand Alone DME) Non-Compulsory Compulsory

BRIEFING STRIP INFORMATION

Cold Weather Symbol 

EXPLANATION OF VFR TERMS AND SYMBOLS


This chapter covers the Sectional Aeronautical Chart (Sectional). These charts include the most current data at a scale of (1:500,000) which is large enough to be read easily by pilots flying by sight under Visual Flight Rules. Sectionals are named after a major city within its area of coverage.

The chart legend includes aeronautical symbols and information about drainage, terrain, the contour of the land, and elevation. You can learn to identify aeronautical, topographical, and obstruction symbols (such as radio and television towers) by using the legend.

A brief description next to a small black square indicates the exact location for many of the landmarks easily recognized from the air, such as stadiums, pumping stations, refineries, etc. A small black open circle with descriptive type indicates oil, gas or mineral wells. A small black circle with descriptive type indicates water, oil or gas tanks. The scale for some items may be increased to make them easier to read on the chart.

Aeronautical Information Services' charts are prepared in accordance with specifications of the Interagency Air Committee (IAC) and are approved by representatives of the Federal Aviation Administration (FAA) and the Department of Defense (DoD).

WATER FEATURES (HYDROGRAPHY)



Water features are depicted using two tones of blue, and are considered either "Open Water" or "Inland Water." "Open Water," a lighter blue tone, shows the shoreline limitations of all coastal water features at the average (mean) high water levels for oceans and seas. Light blue also represents the connecting waters like bays, gulfs, sounds and large estuaries.

Exceptionally large lakes like the Great Lakes, Great Salt Lake, and Lake Okeechobee, etc., are considered Open Water features. The Open Water tone extends inland as far as necessary to adjoin the darker blue "Inland Water" tones. All other bodies of water are marked as "Inland Water" in the darker blue tone.

LAND FEATURES (TERRAIN) AND OBSTRUCTIONS

The elevation and configuration of the Earth's surface is important to pilots. Our Aeronautical Information Specialists are devoted to showing the contour of the earth and any obstructions clearly and accurately on our charts. We use five different techniques: contour lines, shaded relief, color tints, obstruction symbols, and Maximum Elevation Figures (MEF).


1. Contour lines join points of equal elevation. On Sectionals, basic contours are spaced at 500' intervals. Intermediate contours are typically at 250' intervals in moderately level or gently rolling areas. Auxiliary contours at 50', 100', 125', or 150' intervals occasionally show smaller relief features in areas of relatively low relief. The pattern of these lines and their spacing gives the pilot a visual concept of the terrain. Widely spaced contours represent gentle slopes, while closely spaced contours represent steep slopes.
2. Shaded relief shows how terrain may appear from the air. Shadows are shown as if light is coming from the northwest, because studies have shown that our visual perception has been conditioned to this view.
3. Different color tints show bands of elevation relative to sea level. These colors range from light green for the lower elevations, to dark brown for the higher elevations.



- Obstruction symbols show man made vertical features that could affect safe navigation. FAA's Aeronautical Information Manual (AIM) maintains a database of over 351,148 obstacles in the United States, Canada, the Caribbean, Mexico and U.S. Pacific Island Territories. Aeronautical Specialists evaluate each obstacle based on charting specifications before adding it to a visual chart. When a Specialist is not able to verify the position or elevation of an obstacle, it is marked UC, meaning it is "under construction" or being reported, but has not been verified.

The FAA uses a Digital Obstacle File (DOF) to collect and disseminate data. Because land and obstructions frequently change, the source data on obstructions and terrain is occasionally incomplete or not accurate enough for use in aeronautical publications. For example, when the FAA receives notification about an obstruction, and there is insufficient detail to determine its position and elevation, the FAA Flight Edit Program conducts an investigation.

The Flight Edit crew visually verifies the cultural, topographic, and obstacle data. Charts are generally flight-checked every four years. This review includes checking for any obstruction that has been recently built, altered, or dismantled without proper notification.



- Obstacles less than 1000' AGL. Sectional Charts, Terminal Area (TACs) and Caribbean Charts (CACs) typically show manmade obstacles extending more than 200' Above Ground Level (AGL), or more than 299' AGL in yellow city tint. Features considered to be hazardous obstacles to low-level flight are; smokestacks, tanks, factories, lookout towers, and antennas, etc. On World Aeronautical Charts (WACs) only those obstacles at 500' AGL and higher are charted.
- Obstacles 1000' AGL or greater. On World Aeronautical Charts (WACs) only those obstacles at 500' AGL and higher are charted.

5540 (650) Manmade features used by FAA Air Traffic Control as checkpoints use a graphic symbol shown in black with the required elevation data in blue. The elevation of the top of the obstacle above Mean Sea Level (MSL) and the height of the structure (AGL) is also indicated (when known or can be reliably determined by a Specialist). The AGL height is in parentheses below the MSL elevation. In extremely congested areas, the FAA typically omits the AGL values to avoid confusion.

GARFIELD STACK

4977 (1432) Whenever possible, the FAA depicts specific obstacles on charts. However, in high-density areas like city complexes, only the highest obstacle is represented on the chart using the group obstacle symbol to maximize legibility.

Group Obstacle Symbol

Obstacles under construction are indicated by placing the letters UC adjacent to the obstacle type.

Obstacles with high-intensity strobe lighting systems may operate part-time or by proximity activation and are shown as follows:

Guy wires may extend outward from obstacles.

5000 (1500) UC
If space is available, the AGL height of the obstruction is shown

- The Maximum Elevation Figure (MEF) represents the highest elevation within a quadrant, including terrain and other vertical obstacles (towers, trees, etc.). A quadrant on Sectionals is the area bounded by ticked lines dividing each 30 minutes of latitude and each 30 minutes of longitude. MEF figures are rounded up to the nearest 100' value and the last two digits of the number are not shown.

12⁵
In this example the MEF represents 12,500'.

MEFs over land and open water areas are used in areas containing manmade obstacles such as oil rigs.

In the determination of MEFs, the FAA uses extreme care to calculate the values based on the existing elevation data shown on source material. Aeronautical Information Specialists use the following procedure to calculate MEFs:

MEF - Manmade Obstacle

When a manmade obstacle is more than 200' above the highest terrain within the quadrant:

1. Determine the elevation of the top of the obstacle above MSL.
2. Add the possible vertical error of the source material to the above figure (100' or 1/2 contour interval when interval on source exceeds 200'. U.S. Geological Survey Quadrangle Maps with contour intervals as small as 10' are normally used).
3. Round the resultant figure up to the next higher hundred-foot level.

Example:

Elevation of obstacle top (MSL)	2649
Possible obstacle error	+100
equals	2749
Raise to the following 100' level	2800
Maximum Elevation Figure (MEF)	28




MEF - Natural Terrain Feature or Natural Vertical Obstacle

When a natural terrain feature or natural vertical obstacle (e.g. a tree) is the highest feature within the quadrangle:

1. Determine the elevation of the feature.
2. Add the possible vertical error of the source to the above figure (100' or 1/2 the contour interval when interval on source exceeds 200').
3. Add a 200' allowance for uncharted natural or manmade obstacles. Chart specifications don't require the portrayal of obstacles below minimum height.
4. Round the figure up to the next higher hundred-foot level.

Example:


Elevation of obstacle top (MSL)	13161
Possible vertical error	+100
Obstacle Allowance	+200
equals	13461
Raise to the following 100' level	13500
Maximum Elevation Figure (MEF)	135



Pilots should be aware that while the MEF is based on the best information available to the Specialist, the figures are not verified by field surveys. Also, users should consult the Aeronautical Chart Bulletin in the Chart Supplement or Aeronautical Information Services website to ensure that your chart has the latest MEF data available.


RADIO AIDS TO NAVIGATION

On VFR Charts, information about radio aids to navigation (NAVAID) are boxed, as illustrated. Duplication of data is avoided. When two or more radio aids in a general area have the same name with different frequencies, Tactical Air Navigation (TACAN) channel numbers, or identification letters, and no misinterpretation can result, the name of the radio aid may be indicated only once within the identification box. Very High Frequency/Ultra High Frequency (VHF/UHF) NAVAID names and identification boxes (shown in blue) take precedence. Only those items that differ (e.g., frequency, Morse Code) are repeated in the box in the appropriate color. The choice of separate or combined boxes is made in each case on the basis of economy of space and clear identification of the radio aids.



A NAVAID that is physically located on an airport may not always be represented as a typical NAVAID symbol. A small open circle indicates the NAVAID location when collocated with an airport icon.

The type of NAVAID will be identified by: "VOR," (VHF Omni-Directional Range) "VORTAC" (VOR Tactical Aircraft Control), "VOR-DME," (VOR-Distance Measuring Equipment) or "DME" (Distance Measuring Equipment) positioned on and breaking the top line of the NAVAID box.



DMEs are shown without the compass rose.

AIRPORTS

Airports in the following categories are charted as indicated (additional symbols are shown later in this Section).
Public use airports:

- Hard-surfaced runways greater than 8069' or some multiple runways less than 8069'
- Hard-surfaced runways 1500' to 8069'
- Other than hard-surfaced runways
- Seaplane bases

Military airports:

- Other than hard-surfaced runways

Hard-surfaced runways are depicted the same as public-use airports.

U.S. military airports are identified by abbreviations such as AAF (Army Air Field), AFB (Air Force Base), MCAS (Marine Corps Air Station), NAS (Naval Air Station), NAV (Naval Air Facility), NAAS (Naval Auxiliary Air Station), etc. Canadian military airports are identified by the abbreviation DND (Department of National Defense).

Fuel Available:


- Tick marks around the basic airport symbol indicate that fuel is available Monday through Friday 10:00 AM to 4:00 PM local time.

Other airports with or without fuel:

- H
- F
- U
- R
- X

Airports are plotted in their true geographic position unless the symbol conflicts with a NAVAID at the same location. In such cases, the airport symbol will be displaced, but the relationship between the airport and the NAVAID will be retained.

Airports are identified by their designated name. Generic parts of long airport names (such as "airport," "field," or "municipal") and the first names of persons are commonly omitted unless they are needed to distinguish one airport from another with a similar name.



The figure at right illustrates the coded data that is provided along with the airport name.

The elevation of an airport is the highest point on the usable portion of the landing areas. Runway length is the length of the longest active runway, including displaced thresholds and excluding overruns. Runway length is shown to the nearest 100', using 70 as the rounding point; a runway 8070' in length is charted as 81, while a runway 8069' in length is charted as 80. If a seaplane base is collocated with an airport, there will be additional seaplane base water information listed for the elevation, lighting and runway.

FSS
 NO SVFR
 [NAME](NAM) (PNAM)
 CT - 118.3 * Ⓞ
 ASOS/AWOS 135.42
 897 L 110 122.95 — UNICOM
 RP 23, 34
 VFR Advsy 125.0
 WX CAM
 AOE

<i>Flight Service Station on field</i>	FSS	<i>Elevation in feet</i>	897
<i>Airports where fixed wing special VFR operations are prohibited (shown above airport name) FAR 91</i>	NO SVFR	<i>Lighting in operation Sunset to Sunrise</i>	L
<i>Indicates FAR 93 Special Air Traffic Rules and Airport Traffic Pattern</i>		<i>Lighting limitations exist; refer to Chart Supplement</i>	*L
<i>Location Identifier</i>	(NAM)	<i>Length of longest runway in hundreds of feet; usable length may be less.</i>	72
<i>ICAO Location Identifier</i>	(PNAM)	<i>Aeronautical advisory station</i>	122.95
<i>Control Tower (CT) - primary frequency</i>	CT - 118.3	<i>Runways with Right Traffic Patterns (public use)</i>	RP 23,34
<i>Star indicates operation part-time. See tower frequencies tabulation for hours of operation</i>	*	<i>See Chart Supplement</i>	RP*
<i>Follows the Common Traffic Advisory Frequency (CTAF)</i>	Ⓞ	<i>VFR Advisory Service Shown when ATIS is not available and frequency is other than the primary CT frequency.</i>	VFR Advsy 125.0
<i>Automatic Terminal Information Services</i>	ATIS 123.8	<i>Weather Camera (Alaska)</i>	WX CAM
<i>Automatic Flight Information Service</i>	AFIS 135.2	<i>Airport of Entry</i>	AOE
<i>Automated Surface Weather Observing Systems; shown when full-time ATIS is not available.</i>	ASOS/AWOS 135.42	<i>When information is lacking, the respective character is replaced by a dash. Lighting codes refer to runway edge lights and may not represent the longest runway or full length lighting.</i>	

Airports with Control Towers (CT) and their related data are shown in blue. All other airports and their related data are shown in magenta. The **L** symbol indicates that runway lights are on from dusk to dawn. ***L** indicates that the pilot must consult the Chart Supplement to determine runway lighting limitations, such as: available on request (by radio-call, letter, phone, etc), part-time lighting, or pilot/airport controlled lighting. Lighting codes refer to runway edge lights. The lighted runway may not be the longest runway available, and lights may not be illuminated along the full length of the runway. The Chart Supplement has a detailed description of airport and air navigation lighting aids for each airport. A dash represents no runway edge lights.

The symbol **★** indicates the existence of a rotating or flashing airport beacon operating from dusk to dawn. The Aeronautical Information Manual (AIM) thoroughly explains the types and uses of airport lighting aids.

Right traffic information is shown using the abbreviation 'RP' for right pattern, followed by the appropriate runway number(s) (RP 18). Special conditions or restrictions to the right pattern are indicated by the use of an asterisk (RP*) to

direct the pilot to the Chart Supplement for special instructions and/or restrictions.

The type "OBJECTIONABLE" associated with an airport symbol indicates that an objectionable airspace determination has been made for the airport per FAA JO 7400.2 Section 4, Airport Charting and Publication of Airport Data. Objectionable airspace determinations are based upon a number of factors including conflicting traffic patterns with another airport, hazardous runway conditions, or natural or man-made obstacles in close proximity to the landing area. FAA Regional Airports Offices are responsible for airspace determinations. Address any challenges to objectionable airspace determinations to your FAA Regional Airports Office.

AIRSPACE

CONTROLLED AIRSPACE

Controlled airspace consists of those areas where some or all aircraft may be subject to air traffic control, such as: Class A, Class B, Class C, Class D, Class E Surface (SFC) and Class E Airspace.

Class A Airspace within the United States extends from 18,000' up to 60,000' MSL. While visual charts do not depict Class A, it is important to note its existence.

Class B Airspace is shown in abbreviated form on the World Aeronautical Chart (WAC) and Caribbean Charts (CAC). The Sectional Aeronautical Chart (Sectional) and Terminal Area Chart (TAC) show Class B in greater detail. The MSL ceiling and floor altitudes of each sector are shown in solid blue figures with the last two zeros omitted. Floors extending "upward from above" a certain altitude are preceded by a (+). Operations at and below these altitudes are outside of Class B Airspace. Radials and arcs used to define Class B are prominently shown on TACs. Detailed rules and requirements associated with the particular Class B are shown. The name by which the Class B is shown as **LAS VEGAS CLASS B** for example.

Class B MSL **90**
Altitudes **20**

Class C Airspace is shown in abbreviated form on WACs and Caribbean Charts (CAC). Sectionals and TACs show Class C in greater detail. The MSL ceiling and floor altitudes of each sector are shown in solid magenta figures with the last two zeros eliminated.

Class C MSL **70**
Altitudes **15**

T
SFC The figure at left identifies a sector that extends from the surface to the base of the Class B.

Class C Airspace is identified by name: **BURBANK CLASS C**

Separate notes, enclosed in magenta boxes, give the approach control frequencies to be used by arriving VFR aircraft to establish two-way radio communication before entering the Class C (generally within 20 NM):

CTC BURBANK APP WITHIN
20 NM ON 124,6 395,9

Class C operating less than continuous is indicated by the following note: See NOTAMs/Supplement for Class C eff hrs

Class D Airspace is identified with a blue dashed line. Class D operating less than continuous is indicated by the following note: See NOTAMs/Supplement for Class D eff hrs

Ceilings of Class D are shown as follows: **[30]**

A minus in front of the figure is used to indicate "from surface to, but not including..."

Class E Surface (SFC) Airspace is symbolized with a magenta dashed line. Class E (SFC) operating less than continuous is indicated by the following note: See NOTAMs/Supplement for Class E (sfc) eff hrs

Class E Airspace exists at 1200' AGL unless designated otherwise. The lateral and vertical limits of all Class E, (up to, but not including 18,000') are shown by narrow bands of vignette on Sectionals and TACs.

Controlled airspace floors of 700' above the ground are defined by a magenta vignette; floors other than 700' that laterally abut uncontrolled airspace (Class G) are defined by a blue vignette; differing floors greater than 700' above the ground are annotated by a symbol and a number indicating the floor.

2400 AGL
4500 MSL

CLASS G Class E Airspace with floor 700 ft. above surface that laterally abuts Class G Airspace.
Class E Airspace with floor 700 ft. above surface that laterally abuts 1200 ft. or higher Class E Airspace
Class E Airspace with floor 1200 ft. or greater above surface that laterally abuts Class G Airspace


If the ceiling is less than 18,000' MSL, the value (preceded by the word "ceiling") is shown along the limits of the controlled airspace. These limits are shown with the same symbol indicated above.

UNCONTROLLED AIRSPACE

Class G Airspace within the United States extends up to 14,500' Mean Sea Level. At and above this altitude is Class E, excluding the airspace less than 1500' above the terrain and certain special use airspace areas.

SPECIAL USE AIRSPACE

Special Use Airspace (SUA) confines certain flight activities and restricts entry, or cautions other aircraft operating within specific boundaries. Except for Controlled Firing Areas, SUA areas are depicted on VFR Charts. Controlled Firing Areas are not charted because their activities are suspended immediately when spotter aircraft, radar, or ground lookout positions indicate an aircraft might be approaching the area. Nonparticipating aircraft are not required to change their flight paths. SUA areas are shown in their entirety (within the limits of the chart), even when they overlap, adjoin, or when an area is designated within another area. The areas are identified by type and identifying name/number, and are positioned either within or immediately adjacent to the area.



OTHER AIRSPACE AREAS

Mode C Required Airspace (from the surface to 10,000' MSL) within a 30 NM radius of the primary airport(s) for which a Class B is designated, is depicted by a solid magenta line.



Mode C is required, but not depicted for operations within and above all Class C up to 10,000' MSL.



Enroute Mode C requirements (at and above 10,000' MSL except in airspace at and below 2500' AGL) are not depicted. See FAR 91.215 and the AIM.


FAR 93 Airports and heliports under Federal Aviation Regulation 93 (FAR 93), (Special Air Traffic Rules and Airport Traffic Patterns), are shown by "boxing" the airport name.





TRUCKEE - TAHOE


FAR 91 Airports where fixed wing special visual flight rules operations are prohibited (FAR 91) are shown with the type "NO SVFR" above the airport name.

National Security Areas indicated with a broken magenta line  and Special Flight Rules Areas (SFRAs) indicated with the following symbol: , consist of airspace with defined vertical and lateral dimensions established at locations where there is a requirement for increased security and safety of ground facilities. Pilots should avoid flying through these depicted areas. When necessary, flight may be temporarily prohibited.

The Washington DC Flight Restricted Zone (FRZ) is related to National Security. It is depicted using the Prohibited/Restricted/Warning Area symbology  and is located within the SFRA. It is defined as the airspace within approximately a 13 to 15 NM radius of the DCA VOR-DME. Additional requirements are levied upon aviators requesting access to operate inside the National Capital Region.


Temporary Flight Restriction (TFR) Areas Relating to National Security are indicated with a broken blue line . A Temporary Flight Restriction (TFR) is a type of Notice to Airmen (NOTAM). A TFR defines an area where air travel is restricted due to a hazardous condition, a special event, or a general warning for the entire airspace. The text of the actual TFR contains the fine points of the restriction. It is important to note that only TFRs relating to National Security are charted.

Air Defense Identification Zones (ADIZs) are symbolized using the ADIZ symbol: . As defined in Code of Federal Regulations 14 (CFR 14) Part 99, an ADIZ is an area in which the ready identification, location, and control of all aircraft is required in the interest of national security. ADIZ boundaries include Alaska, Hawaii, Guam, Canada and the Contiguous U.S.

Terminal Radar Service Areas (TRSAs) are shown in their entirety, symbolized by a screened black outline of the entire area including the various sectors within the area .

The outer limit of the entire Terminal Radar Service Areas (TRSA) is a continuous screened black line. The various sectors within the TRSA are symbolized by narrower screened black lines.

Each sector altitude is identified in solid black color by the MSL ceiling and floor values of the respective sector, eliminating the last two zeros. A leader line is used when the altitude values must be positioned outside the respective sectors because of charting space limitations. The TRSA name is shown near the north position of the TRSA as follows: **PALM SPRINGS TRSA**. Associated frequencies are listed in a table on the chart border.

Military Training Routes (MTRs) are shown on Sectionals and TACs. They are identified by the route designator: . Route designators are shown in solid black on the route centerline, positioned along the route for continuity. The designator IR or VR is not repeated when two or more routes are established over the same airspace, e.g., IR201-205-227. Routes numbered 001 to 099 are shown as IR1 or VR99, eliminating the initial zeros. Direction of flight along the route is indicated by small arrowheads adjacent to and in conjunction with each route designator.

The following note appears on Helicopters, Sectionals and TACs except for Hawaiian Islands which is different.

MILITARY TRAINING ROUTES (MTRs)

All IR and VR MTRs are shown, and may extend from the surface upwards. Only the route centerline, direction of flight along the route, and the route designator are depicted - route widths and altitudes are not shown.

Since these routes are subject to change every 56 days, you are cautioned and advised to contact Flight Service for route dimensions and current status for those routes affecting your flight.

Routes with a change in the alignment of the charted route centerline will be indicated in the Aeronautical Chart Bulletin of the Chart Supplement.

DoD users refer to Area Planning AP/1B Military Training Routes North and South America for current routes.

There are IFR (IR) and VFR (VR) routes as follows:

Route identification:

- a. Routes at or below 1500' AGL (with no segment above 1500') are identified by four-digit numbers; e.g., VR1007, etc. These routes are generally developed for flight under Visual Flight Rules.
- b. Routes above 1500' AGL (some segments of these routes may be below 1500') are identified by three or fewer digit numbers; e.g., IR21, VR302, etc. These routes are developed for flight under Instrument Flight Rules.

MTRs can vary in width from 4 to 16 miles. Detailed route width information is available in the Flight Information Publication (FLIP) AP/1B (a Department of Defense publication), or through the 56 Day NASR Subscription from the National Flight Data Center (NFDC).

Special Military Activity areas are indicated on Sectionals by a boxed note in black type. The note contains radio frequency information for obtaining area activity status.

SPECIAL MILITARY ACTIVITY
CTC MOBILE RADIO
ON 123.6
FOR ACTIVITY STATUS

TERMINAL AREA CHART (TAC) COVERAGE

TAC coverage is shown on appropriate Sectionals by a 1/4" masked line as indicated below. Within this area pilots should use TACs, which provide greater detail. A note indicating that the area is on the TAC appears near the masked boundary line.

LOS ANGELES TERMINAL AREA

Pilots are encouraged to use the Los Angeles VFR Terminal Area Chart for flights at or below 10,000'



INSET AND SPECIAL CHART COVERAGE

Inset and Special Chart Coverage (i.e., Grand Canyon Chart) is shown on appropriate Sectionals by a 1/8" masked line as indicated below. A note to this effect appears near the masked boundary line. (Additional examples shown in VFR Sectional and Terminal Charts > Navigational and Procedural Information > Chart Limits.)

If inset chart is on the same chart as outline:

INDIANAPOLIS INSET

See inset chart for additional detail

If inset chart is on a different chart:

INDIANAPOLIS INSET

See inset chart on the St. Louis Sectional for additional information



CHART TABULATIONS

Airport Tower Communications are provided in a columnized tabulation for all tower-controlled airports that appear on the respective chart. Airport names are listed alphabetically. If the airport is military, the type of airfield, e.g., AAF, AFB, NAS, is shown after the airfield name. In addition to the airport name, tower operating hours, primary Very High Frequency/Ultra High Frequency (VHF/UHF) local Control Tower (CT), Ground Control (GND CON), and Automatic Terminal Information Service (ATIS) frequencies, when available, will be given. Airport Surveillance Radar (ASR) and/or Precision Approach Radar (PAR) procedures are listed when available.

Approach Control Communications are provided in a columnized tabulation listing Class B, Class C, Terminal Radar Service Areas (TRSA) and Selected Approach Control Facilities when available. Primary VHF/UHF frequencies are provided for each facility. Sectorization occurs when more than one frequency exists and/or is approach direction dependent. Availability of service hours is also provided.

Special Use Airspace (SUA): Prohibited, Restricted and Warning Areas are presented in blue and listed numerically for U.S. and other countries. Restricted, Danger and Advisory Areas outside the U.S. are tabulated separately in blue. A tabulation of Alert Areas (listed numerically) and Military Operations Areas (MOA) (listed alphabetically) appear on the chart in magenta. All are supplemented with altitude, time of use and the controlling agency/contact facility, and its frequency when available. The controlling agency will be shown when the contact facility and frequency data is unavailable.

Airports with control towers are indicated on the face of the chart by the letters CT followed by the primary VHF tower frequency(ies). Information for each tower is listed in the table below. Operational hours are local time. The primary VHF and UHF tower and ground control frequencies are listed.

Automatic Terminal Information Service (ATIS) frequencies shown on the face of the chart are arrival VHF/UHF frequencies. All ATIS frequencies are listed in the table below. ATIS operational hours may differ from tower operational hours.

ASR and/or PAR indicate Radar Instrument Approach available.

"MON-FRI" indicates Monday through Friday.

O/T indicates other times.

Frequencies (VHF/UHF)

Airport Name	CONTROL TOWER	OPERATES	TOWER	GND CON	ATIS	ASR/PAR
AIRBORNE		0700 MON-1800 SAT 0600-1800 SUN	119.475	121.6	124.925	
BLUE GRASS		CONTINUOUS	119.1 257.8	121.9	126.3	
BOLTON		0730-1930	128.1	121.3 (E) 121.8 (W)		ASR/PAR
CHARLOTTESVILLE-ALBEMARLE		0600-2300	124.5 338.275	121.9 338.275	118.425	PAR
CINCINNATI/NORTHERN KENTUCKY INTL		CONTINUOUS Runway dependent	118.3 (RWYS 18R/36L & 09/27) 118.975 360.85 (RWY 18L/36R)	121.3 (E) 121.7 (W)	134.375 (ARR) 135.3 (DEP)	ASR
COX DAYTON INTL		CONTINUOUS	119.9 257.8	121.9	125.8	
EASTERN WV RGNL/SHEPHERD		0700-2200 TUE-THU 0700-1600 FRI-SAT 1300-1800 SUN O/T BY NOTAM	124.3 236.6	121.8 275.8		

Hours of Operation (local time) Approach direction dependent

Radar Instrument Approach available

Frequencies (VHF/UHF)

CLASS B, CLASS C, TRSA AND SELECTED RADAR APPROACH CONTROL FREQUENCIES

Airspace Name	FACILITY	FREQUENCIES	SERVICE AVAILABILITY
CINCINNATI CLASS B	VHF	119.7 (RWY 09/27 090 -269) (RWY 18R/36L 180 -359)	CONTINUOUS
	UHF	123.875 (RWY 09/27 270 -089) (RWY 18L/36R 360 -179) 363.15	
CHARLESTON CLASS C		124.1 269.125 (N) 119.2 269.125 (S)	CONTINUOUS
COLUMBUS CLASS C		120.2 317.775 (280 -099) 132.3 279.6 (100 -279)	CONTINUOUS
DAYTON CLASS C		127.65 294.5 (360 -090) 118.85 327.1 (091 -180) 134.45 316.7 (181 -359)	CONTINUOUS
BRISTOL TRSA		134.425 349.0 (047 -227) 125.5 317.5 (228 -046) O/T 127.85 371.85 ZTL CNTR	0600-2400 local time
HUNTINGTON TRSA		119.75 257.8 (S) 132.95 257.8 (N)	CONTINUOUS
PERKINSON/BAAF RADAR		118.75 353.9	CONTINUOUS

O/T indicates Other times

Sectors for VHF and UHF traffic

SPECIAL USE AIRSPACE ON SECTIONAL CHART

Unless otherwise noted altitudes are MSL and in feet. Time is local.
"TO" an altitude means "to and including."
FL - Flight Level
NO A/G - No air to ground communications.
Contact nearest FSA for information.

† Other times by NOTAM.
NOTAM - Use of this term in Restricted Areas indicates FAA and DoD NOTAM systems. Use of this term in all other Special Use areas indicates the DoD NOTAM system.

U.S. P-PROHIBITED, R-RESTRICTED, W-WARNING, A-ALERT, MOA-MILITARY OPERATIONS AREA

NUMBER	ALTITUDE	TIME OF USE	CONTROLLING AGENCY/ CONTACT FACILITY	FREQUENCIES — VHF/UHF
R-6602 A	TO BUT NOT INCL 4000	CONTINUOUS MAY 1-SEP 15 †24 HRS IN ADVANCE	WASHINGTON CNTR	118.75 377.1
R-6602 B	4000 TO BUT NOT INCL 11,000	BY NOTAM 24 HRS IN ADVANCE	WASHINGTON CNTR	118.75 377.1
R-6602 C	11,000 TO BUT NOT INCL 18,000	BY NOTAM 24 HRS IN ADVANCE	WASHINGTON CNTR	118.75 377.1

A-220	TO 4000 AGL	0800-2200	NO A/G
-------	-------------	-----------	--------

MOA NAME	ALTITUDE*	TIME OF USE†	CONTROLLING AGENCY/ CONTACT FACILITY	FREQUENCIES — VHF/UHF
BRUSH CREEK	100 AGL TO BUT NOT INCL 5000	0800-2200 MON-SAT	INDIANAPOLIS CNTR	134.0 135.57
BUCKEYE	5000	0800-2200 MON-FRI 0800-1600 SAT-SUN	INDIANAPOLIS CNTR	134.0 135.57
EVERS	1000 AGL	SR-SS BY NOTAM	WASHINGTON CNTR	

*Altitudes indicate floor of MOA. All MOAs extend to but do not include FL 180 unless otherwise indicated in tabulation or on chart.
†Other times by DoD NOTAM.

Sunrise to Sunset

CANADA R-RESTRICTED, D-DANGER AND A-ADVISORY AREA

Restricted	NUMBER	LOCATION	ALTITUDE	TIME OF USE	CONTROLLING AGENCY
Danger	CYR754	CONFEDERATION BRIDGE, PE	TO 500	CONTINUOUS	
Advisory	CYD734	HALIFAX, NS	TO FL 200	OCCASIONAL BY NOTAM	MONCTON ACC
	CYA702 (P)	GREENWOOD, NS	TO 500	CONT DAYLIGHT	
	CYA752 (M)	LIVERPOOL, NS	TO FL 280	CONT DAYLIGHT MON-FRI EXC HOLT†	MONCTON ACC


A-Acrobatc F-Aircraft Test Area H-Hang Gliding M-Military Operations P-Parachuting S-Soaring T-Training

WORLD AERONAUTICAL CHARTS (WAC)

The World Aeronautical Charts are in the process of being discontinued by the FAA. The chart symbology depicted in the Sectional and Terminal Area Chart Section of this Chart Users Guide are similar to those utilized in the WACs.

CARIBBEAN VFR AERONAUTICAL CHARTS (CAC)

Starting in 2016, the FAA CARIBBEAN VFR Aeronautical Charts were first published, replacing the discontinued WACs, parts of CH-25, CJ-26, and CJ-27, with CJ-26's last effective date of 1 February 2018 and CJ-27 last effective date of 29 March 2018. The Caribbean Charts are published as two VFR Charts: Caribbean 1 (CAC-1) covers Southern Florida, Cuba, Haiti and the Bahamas; Caribbean 2 (CAC-2) covers Puerto Rico, Haiti, Dominican Republic, the Lesser Antilles and Leeward Islands. CAC-1 is updated annually and CAC-2 biennially.




Caribbean Charts are designed for VFR and provide aeronautical and topographic information of the Caribbean. The aeronautical information includes airports, radio aids to navigation, Class B airspace and special use airspace. The topographic information includes city tint, populated places, principal roads, drainage patterns and shaded relief.

The chart symbols used on the Caribbean Charts are similar to those used in the Sectional and Terminal Area Charts, the major difference being in scale. The Caribbean VFR Chart scale is 1:1,000,000 vs the Sectional Chart Scale of 1:500,000 and Terminal Area Chart Scale of 1:250,000. Chart symbology will appear smaller on the Caribbean VFR Charts.

Example from Caribbean 1 VFR Aeronautical Chart

Airport Traffic Service and Airport Space Information Unique to CAC

Only airway and reserved airspace effective below 18,000' MSL in the U.S. airspace and below FL200 outside of the U.S. airspace are shown.



VFR SECTIONAL AND TERMINAL AREA CHARTS

GENERAL INFORMATION

The symbols shown in this section illustrate those that appear in the Sectional Aeronautical Charts (Sectionals) and Terminal Area Charts (TACs). The same symbology is utilized in VFR Flyway Planning Charts, Helicopter Route Charts, World Aeronautical Charts (WACs) and Caribbean Aeronautical Charts (CACs), however the scale of the symbols may be different due to the particular chart scales. Where symbology is distinctive to a given chart, examples and explanations are given in the additional examples.

AIRPORTS

Landplane: Civil

Airports having control towers (CT) are shown in blue, all others are shown in magenta.

All recognizable runways, including some which may be closed, are shown for visual identification purposes. Fuel available.


Runway patterns will be depicted at airports with at least one hard surfaced runway 1500' or greater in length.

Non Towered Towered



Landplane: Civil-Military

Non Towered Towered



Landplane: Military

Non Towered Towered

Refueling and repair facilities not indicated.



Heliport

(Selected)

Non Towered Towered



Seaplane: Civil

Non Towered Towered



Ultralight Flight Park

(Selected)



Landplane: Emergency

Fuel not available

or

Complete information is not available.



PUBLIC USE - (Soft surfaced runway, or hard surfaced runway less than 1500' in length.) Fuel not available.



RESTRICTED OR PRIVATE - (Soft surfaced runway, or hard surfaced runway less than 1500' in length.) Use only in emergency, or by specific authorization.



OBJECTIONABLE

OBJECTIONABLE is an airport that has an airspace determination based upon a number of factors including conflicting traffic patterns with another airport, hazardous runway conditions, or natural or man-made obstacles in close proximity to the landing area.



UNVERIFIED - A landing area available but warranting more than ordinary precaution due to:

(1) lack of current information on field conditions,

and/or

(2) available information indicates peculiar operating limitations.



Appropriate note as required for hard surfaced runways only: "(CLOSED)"

ABANDONED - Depicted for landmark value or to prevent confusion with an adjacent usable landing area. (Normally at least 3000' paved).

Seaplane: Emergency




Fuel not available or complete information is not available.

AIRPORTS (Continued)

Airport Data Grouping

(Pvt): Non-public use having emergency or landmark value.


“OBJECTIONABLE”: This airport may adversely affect airspace use.



Flight Service Station on field	FSS	Elevation in feet	897
Airports where fixed wing special VFR operations are prohibited (shown above airport name) FAR 91	NO SVFR	Lighting in operation Sunset to Sunrise	L
Indicates FAR 93 Special Air Traffic Rules and Airport Traffic Pattern		Lighting limitations exist; refer to Chart Supplement	*L
Location Identifier	(NAM)	Length of longest runway in hundreds of feet; usable length may be less.	72
ICAO Location Identifier	(PNAM)	Aeronautical advisory station	122.95
Control Tower (CT) - primary frequency	CT - 118.3	Runways with Right Traffic Patterns (public use)	RP 23,34
Star indicates operation part-time. See tower frequencies tabulation for hours of operation	*	See Chart Supplement	RP*
Follows the Common Traffic Advisory Frequency (CTAF)	C	VFR Advisory Service Shown when ATIS is not available and frequency is other than the primary CT frequency.	VFR Advsy 125.0
Automatic Terminal Information Services	ATIS 123.8	Weather Camera (Alaska)	WX CAM
Automatic Flight Information Service	AFIS 135.2	Airport of Entry	AOE
Automated Surface Weather Observing Systems; shown when full-time ATIS is not available.	ASOS/AWOS 135.42	When information is lacking, the respective character is replaced by a dash. Lighting codes refer to runway edge lights and may not represent the longest runway or full length lighting.	


RADIO AIDS TO NAVIGATION

VOR




VORTAC

When an NDB NAVAID shares the same name and Morse Code as the VOR NAVAID the frequency can be collocated inside the same box to conserve space.



VOR-DME

Hazardous Inflight Weather Advisory Service (HIWAS)



DME




DME co-located at an airport
Note: DMEs are shown without the compass rose.




Compass Rose

Compass Rose is "reference" oriented to magnetic north


Example of VOR NAVAID co-located at airport



Non-Directional Radio Beacon (NDB)



NDB-DME



NAVAID Used To Define Class B Airspace

ILS Components

ILS-DME




TAC - Shown when used in description of Class B airspace.



Compass Rosette

Shown only in areas void of VOR roses.

Compass rosette will be based on the five year epoch magnetic variation model.




RADIO AIDS TO NAVIGATION (Continued)

Automated Weather Broadcast Services

	VHF/UHF	LF/MF
Transcribed Weather Broadcast (TWEB)	T	T
Hazardous Inflight Weather Advisory Services (HIWAS)	H	H
Automated Weather Observing System (AWOS) / Automated Surface Observing System (ASOS)	A	A

Flight Service Station (FSS)

Heavy line box indicates Flight Service Station (FSS). Frequencies 121.5, 122.2, 243.0 and 255.4 (Canada - 121.5, 126.7, and 243.0) are normally available at all FSSs and are not shown above boxes. All other frequencies are shown. Frequencies transmit and receive except those followed by an R.



R - receive only

International Flight Service Station



Off Airport AWOS/ASOS




Broadcast Stations (BS)

On request by the proper authority or when a VFR Checkpoint



Remote Communications Outlet (RCO)

Frequencies above thin line box are remotored to NAVAID site. Other frequencies at FSS providing voice communication may be available determined by altitude and terrain. Consult Chart Supplement for complete information.



Thin line box without frequencies and controlling FSS name indicates no FSS frequency available.

AIRSPACE INFORMATION

Class B Airspace

Sectional

LAS VEGAS CLASS B




Appropriate notes as required may be shown.

Only the airspace effective below 18,000 feet MSL are shown.

(Mode C see FAR 91.215 / AIM)

Terminal Area Chart (TAC)

LAS VEGAS CLASS B



CTC LAS VEGAS APP ON 121.1 OR 257.8

All mileages are nautical (NM).


All radials are magnetic.

AIRSPACE INFORMATION (Continued)

Class C Airspace


Appropriate notes as required may be shown.

(Mode C see FAR 91.215/ AIM)



Class E Airspace

The limits of Class E airspace shall be shown by narrow vignettes or by the dashed magenta symbol. Individual units of designated airspace are not necessarily shown; instead, the aggregate lateral and vertical limits shall be defined by the following:



Airspace beginning at the surface (sfc) designated around airports..

Airspace beginning at 700 feet AGL that laterally abuts 1200 feet or higher Class E Airspace...




Airspace beginning at 700 feet AGL that laterally abuts uncontrolled (Class G) airspace...



Airspace beginning at 1200 feet AGL that laterally abuts uncontrolled (Class G) airspace...




Differentiates floors of airspace greater than 700 feet above the surface...



When the ceiling is less than 18,000 feet MSL, the value prefixed by the word "CEILING", shall be shown along the limits.


Class D Airspace

Altitude in hundreds of feet MSL



See NOTAMS/Supplement for Class D/E (sfc) eff hrs


(A minus in front of the figure is used to indicate "from surface to but not including...")



Airspace beginning at the surface (sfc) designated around airports...



Airspace beginning at the surface with an airspace exclusion area where Class E airspace is excluded below 1200' MSL.



AIRSPACE INFORMATION (Continued)

Class E Airspace (Continued)

Low Altitude Airways VOR and LF/MF (Class E Airspace)

Low altitude Federal Airways are indicated by centerline.

Only the controlled airspace effective below 18,000 feet MSL is shown

Miscellaneous Air Routes




Combined Federal Airway/RNAV 2 "T" Routes are identified in solid blue type adjacent to the solid magenta federal airway identification.

The joint route symbol is screened magenta.

Canadian Airspace

Individual units of designated Canadian airspace are not necessarily shown; instead, the aggregate lateral and vertical limits shall be portrayed as closely as possible to the comparable U.S. airspace.

Appropriate notes as required may be shown



Flight Information Regions (FIR)



Oceanic Control Areas (OCA)



Control Areas (CTA)

Offshore Control Areas



AIRSPACE INFORMATION (Continued)

Special Conservation Areas

National Park, Wildlife Refuge, Primitive and Wilderness Areas, etc.



NOAA Regulated National Marine Sanctuary Designated Areas




Flight operations below 1000' AGL over the designated areas within the Gulf of Farallones National Marine Sanctuary violate NOAA regulations (see 15 CFR 922).

Special Flight Rules Area (SFRA) Relating to National Security

Example: Washington DC


Appropriate notes as required may be shown.

Note: Delimiting line not shown when it coincides with International Boundary, projection lines or other linear features.



WASHINGTON DC METROPOLITAN AREA SFRA


Washington DC Metropolitan Area Special Flight Rules Area/Flight Restricted Zone (DC SFRA & DC FRZ) (See description in Atlantic Ocean).



Temporary Flight Restriction (TFR) Relating to National Security

Example: Washington DC

Appropriate notes as required may be shown.



CAUTION CONTACT FLIGHT SERVICE FOR LATEST FLIGHT RESTRICTION STATUS AND NOTAMS ASSOCIATED WITH P-40 AND R-4009



AIRSPACE INFORMATION (Continued)

Special Flight Rules Area (SFRA)



SPECIAL FEDERAL AVIATION REGULATIONS (SFAR)
14 CFR Part 93, Subpart U and SFAR 50.2 -
GRAND CANYON NATIONAL PARK SPECIAL
FLIGHT RULES AREA. Special regulations apply
to all aircraft operations below 18,000 feet MSL.

Special Use Airspace

Only the airspace effective below 18,000 feet MSL is shown.

The type of area shall be spelled out in large areas if space permits.



PROHIBITED, RESTRICTED or WARNING AREA



ALERT AREA



MILITARY OPERATIONS AREA (MOA)


Special Air Traffic Rules / Airport Patterns (FAR Part 93)

Appropriate boxed note as required shown adjacent to area.



SPECIAL NOTICE
Pilots are required to obtain an ATC clearance prior to entering this area.

Flight Restricted Zone (FRZ) Relating to National Security



FLIGHT RESTRICTED ZONE

National Security Area

Appropriate notes as required may be shown



Small Area

NOTICE
FOR REASONS OF NATIONAL SECURITY
PILOTS ARE REQUESTED TO AVOID FLIGHT
BELOW 1200' MSL IN THIS AREA

Special Awareness Training Areas



NOTICE
Special awareness training required within 60 NM of DCA VOR-DME. See description on Flyway.

Mode C (FAR 91.215)

Appropriate notes as required may be shown.




Air Defense Identification Zone (ADIZ)

Note: Delimiting line not shown when it coincides with International Boundary, projection lines or other linear features.



AIRSPACE INFORMATION (Continued)

High Energy Radiation Areas




Appropriate notes as required may be shown.

Solar Farm-Ocular Glare

Military Training Routes (MTR)

← VR269

Special Military Activity Routes (SMAR)




Boxed notes shown adjacent to route.

SPECIAL MILITARY ACTIVITY
CTC ALBUQUERQUE CNTR ON 135.875
FOR ACTIVITY STATUS

40 / 05 AGL

IFR Routes

Arrival



Departure




Arrival/Departure



TAC only

Special Security Notice Permanent Continuous Flight Restriction Areas



DISNEYLAND THEME PARK
See Note for requirements

Sporting Event Temporary Flight Restriction (TFR) Sites



Space Operations Area (FAR Part 91.143)



Miscellaneous Activity Areas

Aerobic Practice Area



Glider Operations



Hang Glider Activity



Ultralight Activity



Unmanned Aircraft Activity



Parachute Jumping Area with Frequency



Space Launch Activity Area




AIRSPACE INFORMATION (Continued)

VFR Transition Routes

Appropriate notes as required may be shown.


VFR TRANSITION ROUTE
ATC CLEARANCE REQUIRED
SEE SHOWBOAT GRAPHIC
ON SIDE PANEL



Example: Los Angeles



Terminal Radar Service Area (TRSA)




Example: Harrisburg, PA



NAVIGATIONAL AND PROCEDURAL INFORMATION

Isogonic Line and Value

Isogonic lines and values shall be based on the five year epoch magnetic variation model.




Local Magnetic Notes

Unreliability Notes

Magnetic disturbance of as much as 78° exists at ground level and 10° or more at 3000 feet above ground level in this vicinity.

Intersections

Named intersections used as reporting points. Arrows are directed toward facilities which establish intersection.




Aeronautical Lights

By Request

Rotating or Oscillating

Isolated Location

Rotating Light with Flashing Code Identification Light



Rotating Light with Course Lights and Site Number



NAVIGATIONAL AND PROCEDURAL INFORMATION (Continued)

Airport Beacons

Rotating or Flashing




Isolated Locations



VFR Checkpoints

Underline indicates proper name of VFR Checkpoint.



VFR Waypoints

RNAV



Stand-Alone



Collocated with VFR Checkpoint



Obstruction

Above 200' & below 1000' AGL
(above 299' AGL in urban area)




Under Construction (UC) or reported and position/elevation unverified



1000' and higher (AGL)



Wind Turbine



High-Intensity Obstruction Lights

Less than 1000' (AGL)



1000' and higher (AGL)



Wind Turbine



Group obstruction



Wind Turbines



High-intensity lights may operate part-time or by proximity activation.

Marine Lights

With Characteristics of Light

- Red
- White
- Green
- Blue
- Sector
- Fixed
- Single Occulting
- Group Occulting
- Composite Group Occulting
- Isophase
- Flashing
- Group Flashing
- Composite Group Flashing
- Quick
- Interrupted Quick
- Morse Code
- Fixed and Flashing
- Alternating
- Group
- Long Flash
- Group Quick Flashing
- Interrupted Quick Flashing
- Very Quick Flashing
- Group Very Quick Flashing
- Interrupted Very Quick Flashing
- Ultra Quick Flashing
- Interrupted Ultra Quick Flashing

- Oc
- R SEC
- Land Light
- R
- *W
- G
- B
- SEC
- F
- Oc
- Oc (2)
- Oc (2+1)
- Iso
- FI
- FI (2)
- FI (2+1)
- Q
- IQ
- Mo (A)
- FFI
- AI
- Gp
- LFI
- Q (3)
- IQ
- VQ
- VQ (3)
- IVQ
- UQ
- IUQ

*** Marine Lights are white unless otherwise noted. Alternating lights are red and white unless otherwise noted.**

Group Obstruction

Above 200' & below 1000' AGL
(above 299' AGL in urban area)




1000' and higher (AGL)



At least two in group
1000' and higher (AGL)




Wind Turbines



Wind Turbine Farms

When highest wind turbine is unverified, UC will be shown after MSL value.



Maximum Elevation Figure (MEF)

(see VFR Terms tab for explanation)

135

NAVIGATIONAL AND PROCEDURAL INFORMATION (Continued)

Chart Limits

Outline on Sectional of Terminal Area Chart



LOS ANGELES TERMINAL AREA
Pilots are encouraged to use the Los Angeles VFR Terminal Area Chart for flights at or below 10,000'

Outline of Special Chart on Sectional and Terminal Area Chart



Outline on Sectional of Inset Chart



If Inset chart is on the same chart as outline:

INDIANAPOLIS INSET
See inset chart for additional detail

If inset chart is on a different chart:

INDIANAPOLIS INSET
See inset chart on the St. Louis Sectional for additional information

CULTURE

Railroads


Single Track




Double Track




More Than Two Tracks



Electric



Non-operating, Abandoned or Under Construction



Roads

Dual-Lane Divided Highway Category 1



Primary Category 2



Secondary Category 2



Trails


Category 3




Provides symbolization for dismantled railroad when combined with label "dismantled railroad."

Railroad Yards

Limiting Track To Scale




Location Only



Railroad Stations



Railroad Sidings and Short Spurs



Road Markers

Interstate Route No.



U.S. Route No.



Air Marked Identification Label



Road Names

LINCOLN HIGHWAY

Roads Under Construction




CULTURE (Continued)

Related Features to Railroads and Roads

Bridges and Viaducts

Railroad



Bridges and Viaducts


Road



Causeways



Ferries, Ferry Slips and Fords



Overpasses and Underpasses



Tunnels-Road and Railroad



Populated Places

Yellow tinted areas indicate populated places.

Small circle indicates an area too small to depict using yellow tint.



Font Style and Size indicate the category of the populated area:

Large Cities Category 1
- population more than 250,000

ST LOUIS

Cities and Large Towns Category 2
- population 25,000 to 250,000

NASHVILLE

Towns and Villages Category 3
- population less than 25,000

Frankfort

CULTURE (Continued)

BOUNDARIES


International



State or Province




Convention or Mandate Line



Miscellaneous Cultural Features


Dams




Passable Locks



Weirs and Jetties



Breakwaters



Pipelines



Underground



Landmark Features

- substation
- fort
- cemetery

Mines or Quarries

Shaft Mines or Quarries



Wells


Other than water



Lookout Towers
(Elevation Base of Tower)



Aerial Cableways, Conveyors, Etc.



Time Zones

- PST (+7DT) = UTC
- MST (+6DT) = UTC


Date Line




Dam Carrying Road




Small Locks



Seawalls



Piers, Wharfs, Quays, etc.



Power Transmission and Telecommunication Lines



Tanks

- water
- oil
- gas

Outdoor Theater




Race Tracks



Coast Guard Station




Landmark Areas




HYDROGRAPHY

Open Water



Open/Inland Water



Lakes

Label as required.




Perennial

When too numerous to show individual lakes, show representative pattern and descriptive note. Number indicates elevation.




Non-Perennial

(dry, intermittent, etc.) Illustration includes small perennial lake.



Reservoirs

Natural Shorelines



Man-made Shorelines


Label when necessary for clarity



Too small to show to scale



Under Construction



Inland Water



Shorelines

Definite



Fluctuating



Unsurveyed
Indefinite



Man-made



HYDROGRAPHY (Continued)

Streams


Perennial



Non-Perennial



Fanned Out




Alluvial fan

Braided




Disappearing




Seasonally Fluctuating

with undefined limits



with maximum bank limits, prominent and constant



Sand Deposits in and along riverbeds



Wet Sand Areas

Within and adjacent to desert areas



Aqueducts

To Scale



Abandoned or Under Construction




Underground



Falls

Double-Line



Single-Line



Canals

To Scale



Abandoned or Under Construction




Abandoned to Scale



Small Canals and Drainage / Irrigation Ditches


Perennial




Non-Perennial



Abandoned or Ancient Numerous



Representative pattern and/or descriptive note.



Suspended or Elevated



Tunnels




Kanats

Underground with Air Vents



Rapids

Double-Line




Single-Line




HYDROGRAPHY (Continued)

Salt Evaporators and Salt Pans Man Exploited



Hummocks and Ridges



Peat Bogs



Rice Paddies

Extensive areas indicated by label only.




Springs, Wells and Waterholes




Permanent Snow and Ice Areas

Glaciers




Glacial Moraines



Ice Cliffs




Snowfields, Ice Fields And Ice Caps




Foreshore Flats

Tidal flats exposed at low tide.




Swamps, Marshes and Bogs



Mangrove And Nipa



Cranberry Bogs



Land Subject To Inundation



Tundra


tundra

Ice

Permanent Polar Ice


Pack Ice

Ice Peaks




HYDROGRAPHY (Continued)

Reefs-Rocky or Coral



Fish Ponds and Hatcheries



RELIEF

Contours

Basic



Approximate




Intermediate



Auxiliary



Depression
(Illustration includes mound within depression)



Values




Sand or Gravel Areas



Sand Dunes


To Scale



Hauchering



Miscellaneous Underwater Features Not Otherwise Symbolized



Wrecks

Exposed



Rocks-Isolated

Bare or Awash




Spot Elevations

Position Accurate



Position Accurate, Elevation Approximate




Highest in General Area




Highest on Chart



Mountain Pass



Distorted Surface Areas




Lava Flows



Sand Ridges

To Scale



Shaded Relief



RELIEF (Continued)

Quarries To Scale




Craters



Unsurveyed Areas

Label appropriately as required



Levees And Eskers



Rock Strata Outcrop




Strip Mines, Mine Dumps And Tailings

To Scale




Escarpments, Bluffs, Cliffs, Depressions, Etc.



Uncontoured Areas

Label appropriately as required



VFR FLYWAY PLANNING CHARTS

GENERAL INFORMATION


VFR Flyway Planning Charts are printed on the reverse sides of the Baltimore-Washington, Charlotte, Chicago, Cincinnati, Dallas-Ft. Worth, Denver, Detroit, Houston, Las Vegas, Los Angeles, Miami, Orlando, New Orleans, Phoenix, St. Louis, Salt Lake City, San Diego, San Francisco and Seattle Terminal Area Charts (TACs). The scale is 1:250,000, with area of coverage the same as the associated TACs. Flyway Planning Charts depict flight paths and altitudes recommended for use to by-pass areas heavily traversed by large turbine-powered aircraft. Ground references on these charts provide a guide for visual orientation. VFR Flyway Planning charts are designed for use in conjunction with TACs and are not to be used for navigation.

AIRPORTS

Landplane

No distinction is made between airports with fuel and those without fuel. Runways may be exaggerated to clearly portray the pattern. Hard-surfaced runways which are closed but still exist are included in the charted pattern.

FAR 91 - Fixed wing special VFR operations prohibited.



Landplane (continued)

(Pvt): Non-public use having emergency or landmark value.



“OBJECTIONABLE”: This airport may adversely affect airspace use.



ABANDONED - Depicted for landmark value or to prevent confusion with an adjacent usable landing area. Only portrayed beneath or close to the VFR flyway routes or requested by the FAA. (Normally at least 3000' paved).



RADIO AIDS TO NAVIGATION

VHF Omni-Directional Radio Range (VOR)



VORTAC



VOR-DME



DME




Example: DME co-located at an airport.



Non-Directional Radio Beacon (NDB)




NDB-DME



NAVAIDS Used to Define Class Airspace

ILS - DME



Shared ILS - DME



AIRSPACE INFORMATION


Class B Airspace

Appropriate notes as required may be shown.

(Mode C see FAR 91.215/AIM)


All mileages are nautical (NM).

All radials are magnetic.



Floors extending “upward and above” a certain altitude are preceded by a +. Operations at or below these altitudes are outside of the Class B Airspace.)

Class D Airspace



(A minus sign in front of the figure used to indicate “from surface to but not including...”)

ALTITUDE IN HUNDREDS OF FEET MSL.

Special Airspace Areas

Special Flight Rules Area (SFRA) Relating to National Security

Example: Washington DC


Appropriate notes as required may be shown.

Note: Delimiting line not shown when it coincides with International Boundary, projection lines or other linear features.



Class C Airspace

Appropriate notes as required may be shown.

(Mode C see FAR 91.215/AIM)




Class E Surface (SFC) Airspace



AIRSPACE INFORMATION (Continued)

Flight Restricted Zone (FRZ) Relating To National Security


Example: Washington DC



Temporary Flight Restriction (TFR) Relating To National Security


Example: Washington DC

Appropriate notes as required may be shown.




Special Use Airspace

Only the airspace effective below 18,000 feet MSL is shown.



PROHIBITED, RESTRICTED or WARNING AREA

The type of area shall be spelled out in large areas if space permits.



MILITARY OPERATIONS AREA (MOA) or ALERT AREA

Air Defense Identification Zone (ADIZ)

Note: Delimiting line not shown when it coincides with International Boundary, projection lines or other linear features.




AIRSPACE INFORMATION (Continued)

Special Air Traffic Rules/Airport Traffic Areas (FAR Part 93)

Appropriate boxed note as required shown adjacent to area.



Terminal Radar Service Area (TRSA)



IFR Routes

Arrival



Departure



Arrival/Departure



VFR Transition Routes

Appropriate notes as required may be shown.

VFR TRANSITION ROUTE
ATC CLEARANCE REQUIRED
SEE SHOWBOAT GRAPHIC
ON SIDE PANEL

Uni-directional



Bi-directional



Bi-directional with NAVAID Ident and Radial



Special Conservation Areas


NOAA Regulated National Marine Sanctuary Designated Areas



Flight operations below 1000' AGL over the designated areas within the Gulf of Farallones National Marine Sanctuary violate NOAA regulations (see 15 CFR 922).

Mode C (FAR 91.215)

Appropriate notes as required may be shown.



Sporting Event Temporary Flight Restriction (TFR) Sites



Miscellaneous Activity Areas

Aerobatic Practice Area



Glider Operations



Hang Glider Activity



Ultralight Activity



Unmanned Aircraft Activity




Parachute Jumping Area with Frequency




Space Launch Activity Area



Example: Los Angeles



Suggested VFR Flyway And Altitude




Military Training Routes (MTR)



NAVIGATIONAL AND PROCEDURAL INFORMATION

VFR Checkpoints

Underline indicates proper name of VFR Checkpoint



VFR Waypoints


Stand-Alone



Collocated with VFR Checkpoint



Navigational Data



CULTURE


Railroads

Single and Multiple Tracks



Populated Places

Built-up Areas



Towns



BOUNDARIES


International



Obstructions

Only obstacles greater than 999' above ground level (AGL) or specified by the local ATC Facility shall be shown.

AGL heights are not shown. High-intensity lights may operate part-time or by proximity activation.



Under Construction or reported and position/elevation unverified.

CULTURE


Railroads

Single and Multiple Tracks



Populated Places

Built-up Areas



Towns



BOUNDARIES

International



Roads

Dual-Lane



Divided Highway Primary



Prominent Pictorials



Power Transmission Lines



Landmarks




HYDROGRAPHY

Shorelines



Reservoirs



Major Lakes and Rivers



RELIEF

Spot Elevations

Position Accurate
Mountain Peaks



HELICOPTER ROUTE CHARTS

GENERAL INFORMATION

Helicopter Route Charts are three-color charts that depict current aeronautical information useful to helicopter pilots navigating in areas with high concentrations of helicopter activity. Information depicted includes helicopter routes, four classes of heliports with associated frequency and lighting capabilities, NAVAIDS, and obstructions. In addition, pictorial symbols, roads, and easily-identified geographical features are portrayed. The scale is 1:125,000. These charts are updated every three years or as needed to accommodate major changes.

AIRPORTS

Landplane

All recognizable runways, including some which may be closed, are shown for visual identification.



Public



Private



Unverified



Abandoned



Seaplane



Airport Data Grouping

Boxed airport name indicates airport for which a Special Traffic Rule has been established.

(Pvt): Non-public use having emergency or landmark value. "OBJECTIONABLE": This airport may adversely affect airspace use.

Flight Service Station on field

FSS

Airspace where fixed wing special visual flight rules operations are prohibited (shown above airport name) FAR 91

NO SVFR

Indicates FAR 93 Special Air Traffic Rules and Airport Traffic

NAME

Location Identifier

(NAM)

ICAO Location Identifier

(PNAM)

Control Tower (CT) - primary frequency

CT - 119.1

Star indicates operation part-time. See tower frequencies tabulation for hours of operation

*

When lighting is lacking, the respective character is replaced by a dash.

Lighting codes refer to runway edge lights and may not represent the longest runway or full length lighting. Dashes are not shown on heliports or helipads unless additional information follows the elevation (e.g. UNICOM, CTAF).

Heliport

Heliports public and private



Hospital Helipads



Trauma Center



Helipads located at major airports (when requested)



Ultralight Flight Park



FSS
NO SVFR
NAME (NAM) (PNAM)
CT - 119.1 * (119.8 HELI)
ATIS 115.4
ASOS/AWOS 135.42
285 L 122.95
(Unverified)
AOE

Automated Terminal Information Service

ATIS 115.4

Automated Surface Weather Observing Systems (shown when full-time ATIS is not available). Some ASOS/AWOS facilities may not be located at airports.

ASOS/AWOS 135.42

Elevation in feet

285

Lighting in operation Sunset to Sunshine

L

Lighting limitations exists, refer to Chart Supplement

L

UNICOM - Aeronautical advisory station

122.95

Follows the Common Traffic Advisory Frequency (CTAF)

C

Unverified Heliport

(Unverified)

Airport of Entry

AOE


RADIO AIDS TO NAVIGATION

NAVAIDs


VHF Omni-Directional Radio (VOR) Range

Open circle symbol shown when NAVAID located on airport. Type of NAVAID shown in top of box.

Compass Rose is "reference" oriented to magnetic north.




VOR




VORTAC

When an NDB NAVAID shares the same name and Morse Code as the VOR NAVAID the frequency can be collocated inside the same box to conserve space.



VOR-DME



DME




Flight Service Station (FSS)


Heavy line box indicates Flight Service Station (FSS) Frequencies 121.5, 122.2, 243.0 and 255.4 (Canada 121.5, 126.7, and 243.0) are available at many FSSs and are not shown above boxes. All other frequencies are shown.

Certain FSSs provide Airport Advisory Service, refer to Chart Supplement.


R - Receive Only




Non-Directional Radio Beacon (NDB)



NDB-DME



NAVAID Used to Define Class B Airspace



Broadcast Stations (BS)


On request by the proper authority or when a VFR Checkpoint.



Remote Communications Outlet (RCO)

Frequencies above thin line box are remotored to NAVAID site. Other FSS frequencies providing voice communications may be available as determined by altitude and terrain. Consult Chart Supplement for complete information.

Thin line box without frequencies and controlling FSS name indicates no FSS frequency available.



AIRSPACE INFORMATION


Class B Airspace

Appropriate notes as required may be shown. (Mode C see FAR 91.215/AIM)

All mileages are nautical (NM)


(Floors extending "upward from above" a certain altitude are preceded by a +. Operations at and below these altitudes are outside of Class B Airspace.)

All radials are magnetic.



Class C Airspace


Appropriate notes as required may be shown. (Mode C see FAR 91.215/AIM)



Class D Airspace


(A minus in front of the figure is used to indicate "from surface to but not including...")

Altitudes in hundreds of feet MSL.



Class E Surface (SFC) Airspace

See NOTAMs/Supplement for Class E (sfc) eff hrs




Special Airspace Areas

Special Flight Rules Area (SFRA) Relating to National Security

Example: Washington DC

Appropriate notes as required may be shown.

Note: Delimiting line not shown when it coincides with International Boundary, projection lines or other linear features.




AIRSPACE INFORMATION (Continued)

Example: Washington DC

Special Airspace Areas (Continued)

Flight Restricted Zone (FRZ) Relating to National Security



Air Defense Identification Zone (ADIZ)

Note: Delimiting line not shown when it coincides with International Boundary, projection lines or other linear features.

CONTIGUOUS U.S. ADIZ



Special Security Notice Permanent Continuous Flight Restriction Areas



DISNEYLAND THEME PARK
See Panel for requirements


Mode C (FAR 91.215)

Appropriate notes as required may be shown.



Terminal Radar Service Area (TRSA)

Appropriate notes as required may be shown.



80 - Ceiling of TRSA in hundreds of feet MSL
40 - Floor of TRSA in hundreds of feet MSL

Special Air Traffic Rules / Airport Traffic Areas (FAR Part 93)



Appropriate boxed notes as required shown adjacent to area.

SPECIAL NOTICE
Pilots are required to obtain an ATC clearance prior to entering this area.

Sporting Event Temporary Flight Restriction (TFR) Sites



Miscellaneous Activity Areas

Aerobic Practice Area



Glider Operations



Hang Glider Activity



Ultralight Activity



Unmanned Aircraft Activity



Parachute Jumping Area with Frequency




Space Launch Activity Area



AIRSPACE INFORMATION (Continued)

Military Training Routes (MTR)

Police Zones



Helicopter Routes

Primary Route with Route Name and Tower Frequency



Secondary Route



Transition Symbol



Reporting Points

Non-compulsory



Compulsory



Reporting Point Name

BAHAI


Canadian Airspace

Class B, C or D TCA

Airspace Ceiling and Floor


80
40

Class E Control Zone




Special Conservation Areas

National Park, Wildlife Refuge, Primitive and Wilderness Areas, etc.




Special Use Airspace

Only the airspace effective below 18,000 feet MSL is shown.



PROHIBITED, RESTRICTED or WARNING AREA

The type of area shall be spelled out in large areas if space permits.



MILITARY OPERATIONS AREA (MOA) or ALERT AREA

One-way Route



Altitude Changeover Point



Recommended Altitudes

Minimum Altitude

500


Maximum Altitude

500

Recommended Altitude

500

Class B, C or D Control Zone



NOAA Regulated National Marine Sanctuary Designated Areas




Flight operations below 1000' AGL over the designated areas within the Gulf of Farallones National Marine Sanctuary violate NOAA regulations (see 15 CFR 922).

NAVIGATIONAL AND PROCEDURAL INFORMATION

VFR Checkpoints

Underline indicates proper name of VFR Checkpoint.



Obstruction

Above 299' and below 1000' AGL




1000' and higher AGL




High-Intensity Obstruction Lights

High-intensity lights may operate part-time or by proximity activation.



Navigation Data



VFR Waypoints

Stand-Alone



Collocated with VFR Checkpoint



Collocated with VFR Checkpoint & Reporting Point



Group Obstruction

Above 299' and below 1000' AGL




1000' and higher AGL



Wind Turbine Farms

When highest wind turbine is unverified, UC will be shown after MSL value.



Maximum Elevation Figure (MEF)

(see VFR Terms tab for explanation)


124

CULTURE

Railroads




Bridges



Populated Places



Roads



Boundaries



Power Transmission Lines



Prominent Pictorials




Landmarks

- Landmark-stadium, factory, school, etc.
- ⬆ Lookout Tower
- ⚒ Mines or Quarries
- 🏎 Race Track
- 🎪 Outdoor Theater
- Tank-water, oil or gas

VFR AIRSPACE CLASSES

AIRSPACE	CLASS A	CLASS B	CLASS C	CLASS D	CLASS E	CLASS G
Entry Requirements	ATC Clearance	ATC Clearance	ATC clearance for IFR All require radio contact	ATC clearance for IFR All require radio contact	ATC clearance for IFR All require radio contact	None
Minimum Pilot Qualifications	Instrument Rating	Private or Student certification. Local restrictions apply	Student Certificate	Student Certificate	Student Certificate	Student Certificate
Two-Way Radio Communications	Yes	Yes	Yes	Yes	Yes, under IFR flight plan*	Not required*
Special VFR (SVFR) Allowed	No	Yes	Yes	Yes	Yes	N/A
VFR Visibility Minimum	N/A	3 statute miles	3 statute miles	3 statute miles	Below 10,000' MSL 3 statute miles At or above 10,000' MSL 5 statute miles	Below 1200' AGL (regardless of MSL) Day 1 statute miles Night 3 statute miles Above 1200' AGL & below 10,000 MSL Day 1 statute miles Night 3 statute miles Above 1200' AGL & at or Above 10,000 MSL 5 statute miles
VFR Minimum Distance From Clouds	N/A	Clear of clouds	500' below 1000' above 2000' horizontally	500' below 1000' above 2000' horizontally	Below 10,000' MSL 500' below 1000' above 2000' horizontally At or above 10,000' MSL 1000' below 1000' above 1 statute mile horizontally	Below 1200' AGL (regardless of MSL) Day Clear of the Clouds Night 500' below 1000' above 2000' horizontal Above 1200' AGL & below 10,000 MSL Day 500' below 1000' above 2000' horizontally Night 500' below 1000' above 2000' horizontally Above 1200' AGL & at or Above 10,000 MSL 1000' below 1000' above 1 statute mile horizontally
VFR Aircraft Separation	N/A	All	IFR Aircraft	Runway Operations	None	None
Traffic Advisories	Yes	Yes	Yes	Workload permitting	Workload permitting	Workload permitting
Airport Application	N/A	Radar Instrument Approaches Weather Control Tower High Density	Radar Instrument Approaches Weather Control Tower	Instrument Approaches Weather Control Tower	Instrument Approaches Weather	Control Tower

AIRSPACE CLASSIFICATION



U.S. Airspace depiction as shown on Visual Aeronautical Charts

EXPLANATION OF IFR ENROUTE TERMS

FAA charts are prepared in accordance with specifications of the Interagency Air Committee (IAC), and are approved by representatives of the Federal Aviation Administration and the Department of Defense (DoD). Some information on these charts may only apply to military pilots.

The explanations of symbols used on Instrument Flight Rule (IFR) Enroute Charts and examples in this section are based primarily on the IFR Enroute Low Altitude Charts. Other IFR products use similar symbols in various colors. The chart legends portray aeronautical symbols with a brief description of what each symbol depicts. This section provides more details of the symbols and how they are used on IFR Enroute charts.

AIRPORTS

Active airports are shown on IFR Enroute Charts.

Low Charts:

- All IAP Airports are shown on the Low Altitude Charts (US and Alaska).
- Non-IAP Airports are shown on the U.S. Low Altitude Charts (Contiguous US) have a minimum hard surface runway of 3,000'.
- Non-IAP airports are shown on the U.S. Low Altitude Alaska Charts are show if the runway is 3000' or longer, hard or soft surface.
- Public heliports with an Instrument Approach Procedure (IAP) or requested by the FAA or DoD are depicted on the IFR Enroute Low Altitude Charts.
- Seaplane bases requested by the FAA or DoD are depicted on the IFR Enroute Low Altitude Charts.

On IFR Enroute Low Altitude Charts, airport tabulation is provided which identifies airport names, IDs and the panels they are located on.

High Charts:

- Airports shown on the U.S. High Enroute Charts (Contiguous US) have a minimum hard surface runway of 5000'.
- Airports shown on the U.S. High Enroute Alaska Charts have a minimum hard surface runway of 4000'.

Charted airports are classified according to the following criteria:

LOW/HIGH ALTITUDE



Blue - Airports with an Instrument Approach Procedure and/or RADAR MINIMA published in the high altitude DoD Flight Information Publications (FLIPs)

Green - Airports which have an approved Instrument Approach Procedure and/or RADAR MINIMA published in either the U.S. Terminal Procedures Publications (TPPs) or the DoD FLIPs

Brown - Airports without a published Instrument Approach Procedure or RADAR MINIMA

Airports are plotted at their true geographic position.

Airports are identified by the airport name. In the case of military airports, Air Force Base (AFB), Naval Air Station (NAS), Naval Air Facility (NAF), Marine Corps Air Station (MCAS), Army Air Field (AAF), etc., the abbreviated letters appear as part of the airport name.

Airports marked "Pvt" immediately following the airport name are not for public use, but otherwise meet the criteria for charting as specified above.

Runway length is the length of the longest active runway (including displaced thresholds but excluding overruns) and is shown to the nearest 100 feet using 70 feet as the division point; e.g., a runway of 8,070' is labeled 81. The following runway compositions (materials) constitute a hard-surfaced runway: asphalt, bitumen, chip seal, concrete, and tar macadam. Runways that are not hard-surfaced have a small letter "s" following the runway length, indicating a soft surface.

AIRPORT DATA DEPICTION	
<p>Low Altitude</p>	
<p>1. Airport elevation given in feet above or below mean sea level</p> <p>2. Pvt - Private use, not available to general public</p> <p>3. A solid line box enclosed the airport name indicates FAR 93 Special Requirements - see Directory/Supplement</p> <p>4. "NO SVFR" above the airport name indicates FAR 91 fixed-wing special VFR flight is prohibited.</p> <p>5. [C] or [D] following the airport identifier indicates Class C or Class D Airspace</p> <p>High Altitude - U.S.</p>	<p>6. Associated city names for public airports are shown above or preceding the airport name. If airport name and city name are the same, only the airport name is shown. The airport identifier in parentheses follows the airport name. City names for military and private airports are not shown.</p> <p>7. Airport Ident ICAO Location Indicator shown outside contiguous U.S.</p> <p>8. AFIS Alaska only</p> <p>High Altitude - Alaska</p>
<p>LIGHTING CAPABILITY</p> <p>Lighting Available L</p> <p>Pilot Controlled Airport (L)</p>	<p>Part-time or on request ★</p> <p>No lighting available At private facilities- indicates no lighting information is available -</p>







A **L** symbol between the airport elevation and runway length means that runway lights are in operation sunset to sunrise. A **(L)** symbol indicates there is Pilot Controlled Lighting. A **L★** symbol means the lighting is part-time or on request, the pilot should consult the Chart Supplement for light operating procedures. The Aeronautical Information Manual (AIM) thoroughly explains the types and uses of airport lighting aids.

RADIO AIDS TO NAVIGATION

All IFR radio NAVAIDs that have been flight checked and are operational are shown on all IFR Enroute Charts. Very High Frequency/Ultrahigh Frequency (VHF/UHF) NAVAIDs, Very high frequency Omnidirectional Radio range (VORs), Tactical Air Navigation (TACANs) are shown in black, and Low Frequency/Medium Frequency (LF/MF) NAVAIDs, (Compass Locators and Aeronautical or Marine NDBs) are shown in brown.

On IFR Enroute Charts, information about NAVAIDs is boxed as illustrated below. To avoid duplication of data, when two or more NAVAIDs in a general area have the same name, the name is usually printed only once inside an identification box with the frequencies, TACAN channel numbers, identification letters, or Morse Code Identifications of the different NAVAIDs are shown in appropriate colors.

NAVAIDs in a shutdown status have the frequency and channel number crosshatched. Use of the NAVAID status "shut-down" is only used when a facility has been decommissioned but cannot be published as such because of pending airspace actions.


NAVIGATION AND COMMUNICATION BOXES - COMMON ELEMENTS	
LOW ENROUTE CHARTS RCO Frequencies NAVAID Name FREQ, Ident, CH, Morse Code Latitude, Longitude Controlling FSS Name	HIGH ENROUTE CHARTS RCO Frequencies NAVAID Name Frequency, Ident, Channel, Latitude, Longitude Controlling FSS Name
000.0 NAME 000.0 IDT 000 ☰☰ N00°00.00' W000°00.00' [NAME]	000.0 NAME 000.0 IDT 000 N00°00.00' W000°00.00' [NAME]
COMMON ELEMENTS (HIGH AND LOW CHARTS)	
RCO FREQUENCY Single Frequency Multiple Frequencies Frequencies transmit and receive except those followed by R and T: R - Receive Only T - Transmit Only	122.6 255.4 243.0 123.6 122.65 122.2 122.1R 121.5
NAVAID BOX Thin line NAVAID boxes without frequency(s) and FSS radio name indicates no FSS frequencies available. Shadow NAVAID box indicates NAVAID and Flight Service Station (FSS) have same name.	VHF/UHF LF/MF  
FREQUENCY PROTECTION Frequency Protection usable range at 18,000' AGL - 40 NM Frequency Protection usable range at 12,000' AGL - 25 NM	(L) (T)
DISTANCE MEASURING EQUIPMENT Facilities that operate in the "Y" mode for DME reception	(Y)
VOICE COMMUNICATIONS VIA NAVAID Voice Transmitted No Voice Transmitted	112.6 111.0
NAVAID SHUTDOWN STATUS	VHF/UHF LF/MF 
PART TIME OR ON-REQUEST	VHF/UHF LF/MF ★ ★
AUTOMATED WEATHER BROADCAST SERVICES ASOS/AWOS - Automated Surface Observing Station/Automated Weather Observing Station HIWAS - Hazardous Inflight Weather Advisory Service TWEB - Transcribed Weather Broadcast	VHF/UHF LF/MF  Automated weather, when available, is broadcast on the associated NAVAID frequency.
LATITUDE AND LONGITUDE Latitude and Longitude coordinates are provided for those NAVAIDs that make up part of a route/airway or a holding pattern.	LOW ENROUTE  HIGH ENROUTE 

AIRSPACE INFORMATION

CONTROLLED AIRSPACE

Controlled airspace consists of those areas where some or all aircraft are subjected to air traffic control within the following airspace classifications of A, B, C, D, & E.

Air Route Traffic Control Centers (ARTCC) are established to provide Air Traffic Control to aircraft operating on IFR flight plans within controlled airspace, particularly during the enroute phase of flight. Boundaries of the ARTCCs are shown in their entirety using the symbol below.



The responsible ARTCC Center names are shown adjacent and parallel to the boundary line. ARTCC sector frequencies are shown in boxes outlined by the same symbol.



Class A Airspace is depicted as open area (white) on the IFR Enroute High Altitude Charts. It consists of airspace from 18,000 Mean Sea Level (MSL) to 60,000 MSL. In aviation terms those altitudes are written as FL 180 to FL 600, (18,000 MSL, is Flight Level (FL)180, 60,000 MSL, is FL 600).

Class B Airspace is depicted as screened blue area with a solid line encompassing the area.

Class C Airspace is depicted as screened blue area with a dashed line encompassing the area with a following the airport name.

Class B and Class C Airspace consist of controlled airspace extending upward from the surface or a designated floor to specified altitudes, within which all aircraft and pilots are subject to the operating rules and requirements specified in the Federal Aviation Regulations (UHF) 71. Class B and C Airspace are shown in abbreviated forms on IFR Enroute Low Altitude Charts. A general note adjacent to Class B airspace refers the user to the appropriate VFR Terminal Area Chart.

Class D Airspace (airports with an operating control tower) are depicted as open area (white) with a following the airport name.

Class E Airspace is depicted as open area (white) on the IFR Enroute Low Altitude Charts. It consists of airspace below FL180.


UNCONTROLLED AIRSPACE

Class G Airspace within the United States extends to 14,500' MSL. This uncontrolled airspace is shown as screened brown.

On Area Charts any uncontrolled airspace boundaries are depicted with a .012" brown line and a .060" screen brown band on the uncontrolled side, so as to be seen over the terrain.

SPECIAL USE AIRSPACE


Special Use Airspace (SUA) confines certain flight activities, restricts entry, or cautions other aircraft operating within specific boundaries. SUA areas are shown in their entirety, even when they overlap, adjoin, or when an area is designated within another area. SUA with altitudes from the surface and above are shown on the IFR Enroute Low Altitude Charts. Similarly, SUA that extends above 18,000' MSL are shown on IFR Enroute High Altitude Charts. On IFR Enroute Altitude Charts tabulations, identify the type of SUA, ID, effective altitudes, times of use, controlling agency and the panel it is located on.




High and Low	Low Altitude Only	Canada Only	Caribbean Only
P - Prohibited Area	MOA - Military Operations Area	CYA - Advisory	D - Danger
R - Restricted Area	A - Alert Area	CYD - Danger Area	
W - Warning Area		CYR - Restricted Area	
See Airspace Tabulation on chart for complete information.			

OTHER AIRSPACE

FAR 91 Special Air Traffic Rules are shown with the type NO SVFR above the airport name.



FAR 93 Special Airspace Traffic Rules are shown with a solid line box around the airport name, indicating FAR 93 Special Requirements see Chart Supplement.



Mode C Required Airspace (from the surface to 10,000' MSL) within 30 NM radius of the primary airport(s) for which a Class B airspace is designated, is depicted on IFR Enroute Low Altitude Charts as a blue circle labeled MODE C 30 NM.



Mode C is also required for operations within and above all Class C airspace up to 10,000' MSL, but not depicted. See FAR 91.215 and the AIM.

INSTRUMENT AIRWAYS

The FAA has established two fixed route systems for air navigation. The VOR and LF/MF system-designated from 1,200' Above Ground Level (AGL) to but not including FL 180 is shown on IFR Enroute Low Altitude Charts, and the Jet Route system designated from FL 180 to FL 450 inclusive is shown on IFR Enroute High Altitude Charts.

VOR LF/MF AIRWAY SYSTEM (IFR LOW ALTITUDE ENROUTE CHARTS)

In this system VOR airways - airways based on VOR or VORTAC NAVAIDs - are depicted in black and identified by a "V" (Victor) followed by the route number (e.g., "V12").

LF/MF airways - airways based on LF/MF NAVAIDs - are sometimes called "colored airways" because they are identified by color name and number (e.g., "Amber One", charted as "A1"). In Alaska Green and Red airways are plotted east and west, and Amber and Blue airways are plotted north and south. Regardless of their color identifier, LF/MF airways are shown in brown.

AIRWAY/ROUTE DATA

On both series of IFR Enroute Charts, airway/route data such as the airway identifications, magnetic courses bearings or radials, mileages, and altitudes (e.g., Minimum Enroute Altitudes (MEAs), Minimum Reception Altitudes (MRAs), Maximum Authorized Altitudes (MAAs), Minimum Obstacle Clearance Altitudes (MOCAs), Minimum Turning Altitudes (MTAs) and Minimum Crossing Altitudes (MCAs)) are shown aligned with the airway.


As a rule the airway/route data is charted and in the same color as the airway, with one exception. Charted in blue, Global Navigation Satellite System (GNSS) MEAs, identified with a "G" suffix, have been added to "V" and "colored airways" for aircraft flying those airways using Global Positioning System (GPS) navigation.

Airways/Routes predicated on VOR or VORTAC NAVAIDs are defined by the outbound radial from the NAVAID. Airways/Routes predicated on LF/MF NAVAIDs are defined by the inbound bearing.

- **Minimum Enroute Altitude (MEA)** - The MEA is the lowest published altitude between radio fixes that assures acceptable navigational signal coverage and meets obstacle clearance requirements between those fixes. The MEA prescribed for a Federal airway or segment, RNAV low or high route, or other direct route applies to the entire width of the airway, segment, or route between the radio fixes defining the airway, segment, or route. MEAs for routes wholly contained within controlled airspace normally provide a buffer above the floor of controlled airspace consisting of at least 300 feet within transition areas and 500 feet within control areas. MEAs are established based upon obstacle clearance over terrain and manmade objects, adequacy of navigation facility performance, and communications requirements.
- **Minimum Reception Altitude (MRA)** - MRAs are determined by FAA flight inspection traversing an entire route of flight to establish the minimum altitude the navigation signal can be received for the route and for off-course NAVAID facilities that determine a fix. When the MRA at the fix is higher than the MEA, an MRA is established for the fix and is the lowest altitude at which an intersection can be determined.
- **Maximum Authorized Altitude (MAA)** - An MAA is a published altitude representing the maximum usable altitude or flight level for an airspace structure or route segment. It is the highest altitude on a Federal airway, jet route, RNAV low or high route, or other direct route for which an MEA is designated at which adequate reception of navigation signals is assured.
- **Minimum Obstruction Clearance Altitude (MOCA)** - The MOCA is the lowest published altitude in effect between fixes on VOR airways, off-airway routes, or route segments that meets obstacle clearance requirements for a VOR. The MOCA seen on the enroute chart may have been computed by adding the required obstacle clearance (ROC) to the controlling obstacle in the primary area or computed by using a TERPS chart if the controlling obstacle is located in the secondary area. This figure is then rounded to the nearest 100 foot increment (i.e., 2,049 feet becomes 2,000, and 2,050 feet becomes 2,100 feet). An extra 1,000 feet is added in mountainous areas, in most cases.
- **Minimum Turning Altitude (MTA)** - Minimum turning altitude (MTA) is a charted altitude providing vertical and lateral obstruction clearance based on turn criteria over certain fixes, NAVAIDs, waypoints, and on charted route segments. When a VHF airway or route terminates at a NAVAID or fix, the primary area extends beyond that

termination point. When a change of course on VHF airways and routes is necessary, the enroute obstacle clearance turning area extends the primary and secondary obstacle clearance areas to accommodate the turn radius of the aircraft. Since turns at or after fix passage may exceed airway and route boundaries, pilots are expected to adhere to airway and route protected airspace by leading turns early before a fix. The turn area provides obstacle clearance for both turn anticipation (turning prior to the fix) and flyover protection (turning after crossing the fix). Turning fixes requiring a higher MTA are charted with a flag along with accompanying text describing the MTA restriction.

- Minimum Crossing Altitude (MCA)** - An MCA is the lowest altitude at certain fixes at which the aircraft must cross when proceeding in the direction of a higher minimum enroute IFR altitude. MCAs are established in all cases where obstacles intervene to prevent pilots from maintaining obstacle clearance during a normal climb to a higher MEA after passing a point beyond which the higher MEA applies. The same protected enroute area vertical obstacle clearance requirements for the primary and secondary areas are considered in the determination of the MCA.




Victor Route (with RNAV/GPS MEA shown in blue)


AREA NAVIGATION (RNAV) "T" ROUTE SYSTEM

The FAA has created new low altitude area navigation (RNAV) "T" routes for the enroute and terminal environments. The RNAV routes will provide more direct routing for IFR aircraft and enhance the safety and efficiency of the National Air-space System. To utilize these routes aircraft are required to be equipped with IFR approved GNSS. In Alaska, TSO-145a and 146a equipment is required.

Low altitude RNAV only routes are identified by the prefix "T", and the prefix "TK" for RNAV helicopter routes followed by a three digit number (T-200 to T-500). Routes are depicted in blue on the IFR Enroute Low Altitude Charts. RNAV route data (route line, identification boxes, mileages, waypoints, waypoint names, magnetic reference courses and MEAs) will also be printed in blue. Magnetic reference courses will be shown originating from a waypoint, fix/reporting point or NAVAID. GNSS MEA for each segment is established to ensure obstacle clearance and communications reception. GNSS MEAs are identified with a "G" suffix.



Joint Victor/RNAV routes are charted as outlined above except as noted. The joint Victor route and the RNAV route identification boxes are shown adjacent to each other. Magnetic reference courses are not shown. MEAs are charted above the appropriate identification box or stacked in pairs, GNSS and Victor. On joint routes, RNAV specific information will be printed in blue.



OFF ROUTE OBSTRUCTION CLEARANCE ALTITUDE (OROCA)

The Off Route Obstruction Clearance Altitude (OROCA) is depicted on IFR Enroute Low Altitude and Pacific charts and is represented in thousands and hundreds of feet above MSL. OROCA's are shown in every 30 x 30 minute quadrant on Area Charts, every one degree by one degree quadrant for IFR Enroute Low Altitude Charts - U.S. and every two degree by two degree quadrant on IFR Enroute Low Altitude Charts - Alaska. The OROCA represents the highest possible obstruction elevation including both terrain and other vertical obstruction data (towers, trees, etc.) bounded by the ticked lines of latitude/longitude including data 4 NM outside the quadrant. In this example the OROCA represents 12,500 feet.

OROCA is computed just as the Maximum Elevation Figure (MEF) found on Visual Flight Rule (VFR) Charts except that it provides an additional vertical buffer of 1,000 feet in designated non-mountainous areas and a 2,000 foot vertical buffer in designated mountainous areas within the United States. For areas in Mexico and the Caribbean, located outside the U.S. Air Defense Identification Zone (ADIZ), the OROCA provides obstruction clearance with a 3,000 foot vertical buffer. Evaluating the area around the quadrant provides the chart user the same lateral clearance an airway provides should the line of intended flight follow a ticked line of latitude or longitude. OROCA does not provide for NAVAID signal coverage, communication coverage and would not be consistent with altitudes assigned by Air Traffic Control. OROCA's can be found over all land masses and open water areas containing man-made obstructions (such as oil rigs).

12⁵

MILITARY TRAINING ROUTES (MTRs)

Military Training Routes (MTRs) are routes established for the conduct of low-altitude, high-speed military flight training (generally below 10,000 feet MSL at airspeeds in excess of 250 knots Indicated Air Speed). These routes are depicted in brown on IFR Enroute Low Altitude Charts, and are not shown on inset charts or on IFR Enroute High Altitude Charts. IFR Enroute Low Altitude Charts depict all IFR Military Training Routes (IRs) and VFR Military Training Routes (VRs), except those VRs that are entirely at or below 1,500 feet AGL.

MTRs are identified by designators (IR-107, VR-134) which are shown in brown on the route centerline. Arrows are shown to indicate the direction of flight along the route. The width of the route determines the width of the line that is plotted on the chart:

Route segments with a width of 5 NM or less, both sides of the centerline, are shown by a .02" line.



Route segments with a width greater than 5 NM, either or both sides of the centerline, are shown by a .035" line.



MTRs for particular chart pairs (ex. L1/2, etc.) are alphabetically, then numerically tabulated. The tabulation includes MTR type and unique identification and altitude range.

JET ROUTE SYSTEM (HIGH ALTITUDE ENROUTE CHARTS)

Jet routes are based on VOR or VORTAC NAVAIDs, and are depicted in black with a "J" identifier followed by the route number (e.g., "J12"). In Alaska, Russia and Canada some segments of jet routes are based on LF/MF NAVAIDs.

AREA NAVIGATION (RNAV) "Q" ROUTE SYSTEM (IFR Enroute HIGH ALTITUDE CHARTS)


The FAA has adopted certain amendments to Title 14, Code of Federal Regulations which paved the way for the development of new area high altitude navigation (RNAV) "Q" routes in the U.S. National Airspace System (NAS). These amendments enable the FAA to take advantage of technological advancements in navigation systems such as the GPS. RNAV "Q" Route MEAs are shown when other than FL 180 MEAs for DME/DME/Inertial Reference Unit (IRU) RNAV aircraft have a "D" suffix.



RNAV routes and associated data are charted in blue.

"Q" Routes on the IFR Gulf of Mexico charts are shown in black. Magnetic reference courses are shown originating from a waypoint, fix/reporting point, or NAVAID.

Joint Jet/RNAV route identification boxes will be located adjacent to each other with the route charted in black. With the exception of Q-Routes in the Gulf of Mexico, GNSS or DME/DME/IRU RNAV are required, unless otherwise indicated. DME/DME/IRU RNAV aircraft should refer to the Chart Supplement for DME information. Q-Routes in Alaska are GNSS Only. Altitude values are stacked highest to lowest.



TERRAIN CONTOURS ON AREA CHARTS

Based on a recommendation of the National Transportation Safety Board, terrain contours have been added to the Enroute Area Charts and are intended to increase pilots' situational awareness for safe flight over changes in terrain. The following Area Charts portray terrain: Anchorage, Denver, Fairbanks, Juneau, Los Angeles, Nome, Phoenix, San Francisco, Vancouver and Washington.

When terrain rises at least a 1,000 feet above the primary airports' elevation, terrain is charted using shades of brown with brown contour lines and values. The initial contour will be 1,000 or 2,000 feet above the airports' elevation. Subsequent intervals will be 2,000 or 3,000 foot increments.

Contours are supplemented with a representative number of spots elevations and are shown in solid black. The highest elevation on an Area Chart is shown with a larger spot and text.

The following boxed note is added to the affected Area Charts.

NOTE: TERRAIN CONTOURS HAVE BEEN ADDED TO THOSE AREA CHARTS WHERE THE TERRAIN ON THE CHART IS 1000 FOOT OR GREATER THAN THE ELEVATION OF THE PRIMARY AIRPORT

IFR ENROUTE LOW / HIGH ALTITUDE SYMBOLS (U.S., PACIFIC AND ALASKA CHARTS)

AIRPORTS

Airport Data - Low/High Altitude


Civil Charts: High/Low


Seaplane - Civil Charts: Low


Civil And Military Charts: High/Low


Heliport Charts: Low


Military Charts: High/Low


Emergency Use Only
 Pacific Only


Facilities in BLUE or GREEN have an approved Instrument Approach Procedure and/or RADAR MINIMA published in either the FAA Terminal Procedures Publication or the DoD FLIPs. Those in BLUE have an Instrument Approach Procedure and/or RADAR MINIMA published at least in the High Altitude DoD FLIPs. Facilities in BROWN do not have a published Instrument Procedure or RADAR MINIMA.

All IAP Airports are shown on the Low Altitude Charts.

Non-IAP Airports shown on the U.S. Low Altitude Charts have a minimum hard surface runway of 3000'.

Airports shown on the U.S. High Altitude Charts have a minimum hard surface runway of 5000'.

Airports shown on the Alask High Altitude Charts have a minimum hard or soft surface runway of 4000'.


Associated city names for public airports are shown above or preceding the airport name and city name are the same only the airport name is shown. City names for military and private airports are not shown.

The airport identifier in parentheses follows the airport name or Pvt.

Pvt - Private Use

AIRPORT DATA DEPICTION

Low Altitude



1. Airport elevation given in feet above or below mean sea level


2. Pvt - Private use, not available to general public

3. A solid line box enclosed the airport name indicates FAR 93 Special Requirements - see Directory/Supplement

4. "NO SVFR" above the airport name indicates FAR 91 fixed-wing special VFR flight is prohibited.

5. [C] or [D] following the airport identifier indicates Class C or Class D Airspace

High Altitude - U.S.




6. Associated city names for public airports are shown above or preceding the airport name. If airport name and city name are the same, only the airport name is shown. The airport identifier in parentheses follows the airport name. City names for military and private airports are not shown.

7. Airport Ident ICAO Location Indicator shown outside contiguous U.S.

8. AFIS Alaska only

High Altitude - Alaska



Airports (Continued)

LIGHTING CAPABILITY

Lighting Available	L	Part-time or on request	★
Pilot Controlled Airport	Ⓛ	No lighting available At private facilities- indicates no lighting information is available	-

RADIO AIDS TO NAVIGATION


NAVAIDS

VOR	VOR/DME	TACAN	DME	NDB	NDB/DME	Reporting Function
						Non Compulsory Reporting or Off Airway
						Compulsory Reporting


Note: VHF/UHF is depicted in Black. LF/MF is depicted in Brown. RNAV is depicted in Blue

Compass Roses

VHF/UHF



LF/MF



Compass Roses are orientated to Magnetic North of the NAVAID which may not be adjusted to the charted isogonic values.

Compass Locator Beacon

LOW ALTITUDE




Chart Example : Enroute Low L-16 US




RADIO AIDS TO NAVIGATION (Continued)

ILS LOCALIZER

ILS Localizer Course with additional navigation function




ILS Localizer Example with Back Course
(Chart: Enroute Low L-1 US)



VOR/DME RNAV WAYPOINT DATA


HIGH ALTITUDE - ALASKA



NAVIGATION AND COMMUNICATION BOXES - COMMON ELEMENTS


LOW ENROUTE CHARTS

RCO Frequencies
NAVAID Name
FREQ, Ident, CH, Morse Code
Latitude, Longitude
Controlling FSS Name



HIGH ENROUTE CHARTS


RCO Frequencies
NAVAID Name
Frequency, Ident, Channel,
Latitude, Longitude
Controlling FSS Name



COMMON ELEMENTS (HIGH AND LOW CHARTS)

RCO Frequency


Single Frequency



Multiple Frequencies


Frequencies transmit and receive except those followed by R and T:

R - Receive Only T - Transmit Only




NAVAID Box

Thin line NAVAIID boxes without frequency(s) and FSS radio name indicates no FSS frequencies available.



Shadow NAVAIID box indicates NAVAIID and Flight Service Station (FSS) have same name.



RADIO AIDS TO NAVIGATION (Continued)

Navigation And Communication Boxes - Examples (Continued)

LOW ENROUTE CHARTS

VOR/DME

No Voice Communications
(Y) Mode DME

R - Receive only 122.1R
Controlling FSS Name - BUFFALO

Shadow NAVAID Box
FSS Associated with NAVAID

TACAN

TACAN Channels are without
voice but not underlined

Part Time NAVAID

VORTAC

H - HIWAS Available

Shutdown status

DME

DME Channel, Ident, Morse Code,
VHF Frequency

NDB

A - ASOS/AWOS Available

Shutdown status

NDB/DME

No Voice Communications
(Y) Mode DME

T- TWEB Available
Shadow NAVAID Box
FSS Associated with NAVAID

Notes:

HIGH ENROUTE CHARTS

VOR/DME

Off Route (Greyed NAVAID Box
and NAVAID)

Service Volume - L
DME in Y Mode

Shadow NAVAID Box
FSS Associated with NAVAID

TACAN

Off Route

Off Route - Part Time NAVAID
(Greyed NAVAID Box and NAVAID)
Service Volume - L

VORTAC

H - HIWAS Available

Off Route (Greyed NAVAID Box
and NAVAID)
Service Volume - L

DME

NDB

T - TWEB Available

NDB/DME

No Voice Communications
(Y) Mode DME

T-TWEB Available
Shadow NAVAID Box
FSS Associated with NAVAID

Notes: Morse Code is not shown on High NAVAID Boxes.

RADIO AIDS TO NAVIGATION (Continued)

Stand Alone Flight Services and Communication Outlets

Flight Service Station (FSS)

Shadow NAVAID boxes indicate Flight Service Station (FSS) locations. Frequencies 122.2, 255.4 and emergency 121.5 and 243.0 are available at many FSSs and are not shown. All other frequencies are show above the box.

Certain FSSs provide Local Airport Advisory (LAA) on 123.6.

Frequencies transmit and receive except those followed by R and T:

- R - Receive Only
- T - Transmit Only

In Canada, shadow boxes indicate FSSs with standard group frequencies of 121.5, 126.7 and 243.0.

Remote Communications Outlet (RCO)

Thin line NAVAID boxes without frequencies and controlling FSS name indicate no FSS frequencies available. Frequencies positioned above the thin line boxes are remoted to the NAVAID sites. Other frequencies at the controlling FSS named are available, however altitude and terrain may determine their reception.

In Canada, a "D" after the frequency indicates a dial-up remote communications outlet.

Stand Alone AWOS & ASOS

LOW CHARTS

HIGH CHARTS

Stand Alone FSS




Stand Alone FSS




Stand Alone FSS Associated with an Airport



Stand Alone FSS Associated with an Airport




Part-time FSS



Stand Alone FSS within Canadian Airspace




Stand Alone FSS within Canadian Airspace




Stand Alone RCO




Stand Alone RCO



RCO Associated/Co-located with an Airport



RCO Associated/Co-located with an Airport



BOONE AWOS 118.525



STAMPEDE PASS ASOS 135.275







AIRSPACE INFORMATION

Airway/Route Types

Low and High Enroute Airway Data:

VHF/UHF Data is depicted in Black.
 LF/MF Data is depicted in Brown.
 RNAV Route data is depicted in Blue

Low Enroute Charts



See MTR tabulation for altitude range information


All IR and VR MTRs are shown except those VRs at or below 1500' AGL

CAUTION: Inset charts do not depict MTRs


Low and High Enroute Charts



High Enroute Charts



Alaska Q Routes require GNSS and radar surveillance. Within the CONUS, GNSS or DME/DME/IRU RNAV required, unless otherwise indicated. DME/DME/IRU aircraft require radar surveillance. Refer to Chart Supplement for DME information.



Jet Route Centerline by-passing a facility which is not part of that specific route.




















All relative and supporting data shown in brown.

See NOTAMS or appropriate publication for specific information.

Airspace Information (Continued)

FIXES		REPORTING FUNCTION	WAYPOINTS
VHF/UHF	LF/MF	Compulsory Position Reporting	RNAV
		Non-Compulsory Position Reporting	
N25°46.47' W76°16.28'	N29°36.00' W88°01.00'	Fix or Waypoint Coordinates <i>Fix Coordinates are shown for compulsory, offshore and holding fixes.</i> <i>Waypoints Coordinates are shown when waypoint is not part of a RNAV route and when located on or beyond the boundary of the U.S. Continental Control (12 mile limit).</i>	N44°25.36' W64°11.00'
		Off-set arrows indicate facility forming a fix - Arrow points away from the VHF/UHF NAVAID - Arrow points towards the LF/MF NAVAID	N/A
		Distance Measuring Equipment (DME) Fix <i>Denotes DME fix (distance same as airway / route mileage)</i>	N/A
VHF/UHF		Distance Measuring Equipment (DME) Fix <i>Denotes DME fix (encircled mileage shown when not otherwise obvious)</i>	RNAV N/A
		Example: <i>First segment, 5NM; second segment 10NM; total mileage provided in encircled DME arrow.</i>	N/A
			N/A
VHF/UHF	LF/MF	Total Mileages between Compulsory Reporting Points or NAVAIDs <i>Note: All mileages are in Nautical Miles</i>	RNAV N/A
229	149		
54	125	MILEAGE BETWEEN OTHER FIXES, NAVAIDs AND/OR MILEAGE BREAKDOWN	125
		Mileage Breakdown or Computer Navigation Fix (CNF) <i>Five letter identifier in parentheses indicates CNF with no ATC function</i>	N/A
		FACILITY LOCATOR BOATS <i>Crosshatch indicates Shutdown status of NAVAID</i>	N/A
	N/A	RADIAL OUTBOUND FROM A VHF/UHF NAVAID <i>All Radials are magnetic.</i>	N/A
N/A		BEARING INBOUND TO AN LF/MF NAVAID <i>All Bearings are magnetic.</i>	N/A
N/A	N/A	MAGNETIC REFERENCE BEARING , outbound from a NAVAID or Fix <i>Note: Not shown on joint Victor/RNAV or Jet/RNAV Routes.</i>	000 →


Airspace Information (Continued)

VHF/UHF LOW CHARTS	LF/MF LOW CHARTS	MINIMUM ENROUTE ALTITUDE (MEA) All Altitudes Are MSL Unless Otherwise Noted.	RNAV LOW CHARTS
0000	0000	Directional MEAs	0000G
			
HIGH CHARTS	HIGH CHARTS	MEAs are shown on IFR High Altitude Charts when MEA is other than 18,000'.	HIGH CHARTS
MEA-29000	MEA-FL240		MEA for GNSS RNAV aircraft MEA-24000G
			MEA for DME/DME/IRU RNAV aircraft MEA-24000D
<p>LOW CHARTS</p>  <p>HIGH CHARTS</p> 		<p>MINIMUM ENROUTE ALTITUDE (MEA) GAP</p> <p>MEA is established when there is a gap in navigation signal coverage.</p>	N/A
LOW / HIGH CHARTS	LOW / HIGH CHARTS	<p>Maximum Authorized Altitude (MAA)</p> <p>All Altitudes Are MSL Unless Otherwise Noted.</p> <p>MAAs are shown on IFR High Altitude Charts when MAA is other than 45,000'.</p>	LOW / HIGH CHARTS
MAA-00000	MAA-00000		MAA-00000
LOW CHARTS	LOW CHARTS	<p>Minimum Obstruction Clearance Altitude (MOCA)</p> <p>All Altitudes Are MSL Unless Otherwise Noted.</p>	LOW CHARTS
*0000	*0000		*0000
LOW CHARTS	LOW CHARTS	<p>Minimum Turning Altitude (MTA) and Minimum Crossing Altitude (MCA)</p> <p>See Low Enroute Chart Example below for examples of both MTAs and MCAs.</p>	LOW CHARTS
			
		<p>MINIMUM RECEPTION ALTITUDE (MRA)</p>	N/A
		<p>ALTITUDE CHANGE</p> <p>MEA, MOCA and/or MAA change at other than NAVAIDs</p>	
LOW / HIGH CHARTS	LOW / HIGH CHARTS	<p>CHANGEOVER POINT</p> <p>Changeover Point giving mileage to NAVAIDs (Not shown at midpoint locations.)</p>	N/A
			
<p>RADDY N47°04.47' W121°30.97'</p> 	<p>LARCE N39°17.12' W69°18.07'</p> 	<p>HOLDING PATTERNS</p> <p>RNAV Holding Pattern Magnetic Reference Bearing is determined by the isogonic value at the waypoint or fix.</p> <p>Holding Pattern with maximum restriction airspeed 210K applies to altitudes 6000' to and including 14000'. 175K applied to all altitudes. Airspeed depicted is Indicated Airspeed (IAS)</p>	
			

AIRSPACE INFORMATION (Continued)

Enroute Chart Examples

Low Enroute Chart




AIRSPACE INFORMATION (Continued)

Enroute Chart Examples

Low Enroute Chart (Continued)

Reference Number

5




Description

MEA VHF and RNAV Example

MEA for aircraft utilizing VHF NAVAID of 15000'
 MEA for aircraft utilizing RNAV of 13300'
 MOCA of 13300'

6




MCA and MTA Example at a NAVAID

MCA for aircraft traveling West along V520 to cross JAC at 15200'
 MCA for aircraft traveling West along V330 to cross JAC at 13400'
 MTA for aircraft crossing over and turning at JAC:
 Aircraft traveling NW on V328 and turning to V465 on a SW heading must turn at altitude of 15100' or higher.
 Aircraft traveling E on V330 and turning to V520 on a W heading must turn at altitude of 16000' or higher
 Aircraft traveling NE on V465 and turning to V330 on a W heading or turning to V520 on a W heading must turn at altitude of 16000' or higher
 Aircraft traveling E on V520 and turning to V330 on a W heading must turn at altitude of 14200'


Airspace Information (Continued)

Enroute Chart Examples

High Enroute Chart




Reference Number



Description

High RNAV Route with MEA for DME/DME/IRU RNAV Aircraft

MEA of 24,000'




Directional Jet Route with Time Restrictions

Jet Route 34 available between 1100 - 0300Z

AIRSPACE INFORMATION (Continued)

Enroute Chart Examples High Enroute Chart (Continued)

Reference Number



Description

Directional Jet Route with Time Restrictions, MAA and MEA

Jet Route 149 available between 1100 - 0300Z
 MAA - 41,000'
 MEA - 31,000'

AIRSPACE BOUNDARIES

Air Defense Identification Zone (ADIZ)

LOW / HIGH CHARTS

CONTIGUOUS U.S. ADIZ

ALASKA ADIZ
 CANADA ADIZ

Adjoining ADIZ

Air Traffic Service Identification Data

LOW / HIGH CHARTS

CTA
 HOUSTON OCEANIC
 KZHU
 UNLTD
 2500 AMSL
 NEW YORK RADIO
 129.4 2887
 5550 6577 8846 8918
 11396 13297 17907

Ceiling
 Floor
 Call Sign
 Frequency

FIR
 HOUSTON OCEANIC
 KZHU
 UNLTD
 AMSL
 NEW YORK RADIO
 129.4 2887
 5550 6577 8846 8918
 11396 13297 17907

Ceiling
 Floor
 Call Sign
 Frequency

Flight Information Regions (FIR)

LOW / HIGH CHARTS

TORONTO FIR CZYZ
 MONTREAL FIR CZUL
 TORONTO FIR CZYZ

Upper Information Regions (UIR)

Upper Control Areas (UTA)

HIGH ALTITUDE
 MONTERREY UTA/UIR SECTOR 2 MMTY
 MERIDA UTA/UIR SECTOR 1 MMID
 MONTERREY UTA/UIR SECTOR 1 MMTY
 HOUSTON OCEANIC CTA/FIR KZHU
 MONTERREY FIR/UIR MMTY

Adjoining UTA / UIR
 Adjoining FIR and UIR

Air Route Traffic Control Center (ARTCC)

ARTCC Remoted Sites with discrete VHF and UHF frequencies

LOW / HIGH CHARTS

NEW YORK
 WASHINGTON
 NEW YORK
 Barnegat
 132.15

ARTCC Name
 Site Name
 Frequency

Altimeter Setting Change

QNH
 ALTIMETER
 QNE 29.92

Control Areas (CTA)

LOW / HIGH CHARTS

NEW YORK OCEANIC CTA/FIR KZHU
 MIAMI OCEANIC CTA/FIR KZMA

Adjoining CTA

Additional Control Areas

LOW ALTITUDE

CONTROL 1141L

HIGH ALTITUDE

CONTROL 1419 H

AIRSPACE INFORMATION (Continued)

Airspace - U.S.

Class A Open Area (White)

High Chart Only That airspace from 18,000' MSL to and including FL 600, including the airspace overlying the waters within 12 NM of the coast of the contiguous United States and Alaska and designated offshore areas, excluding Santa Barbara Island, Farallon Island, the airspace south of latitude 25° 04'00" N, the Alaska peninsula west of longitude 160°00'00" W, and the airspace less than 1,500' AGL.

Controlled Airspace


That airspace from 18,000' MSL to and including FL 450, including Santa Barbara Island, Farallon Island, the Alaska peninsula west of longitude 160°00'00" W, and designated offshore areas.

Class B

Screened Blue with a Solid Blue Outline

Low Chart Only

Controlled Airspace



That airspace from the surface to 10,000' MSL (unless otherwise designated) surrounding the nation's busiest airports. Each Class B airspace area is individually tailored and consists of a surface area and two or more layers.

Mode C Area


A Solid Blue Outline

Low Chart Only

Controlled Airspace

That airspace within 30 NM of the primary airports of Class B airspace and within 10 NM of designated airports. Mode-C transponder equipment is required. (See FAR 91.215)

Example:



Example:

See Chart example above.


AIRSPACE INFORMATION (Continued)

Airspace - U.S. (Continued)


CLASS C Screened Blue with a Solid Blue Dashed Outline

Low Chart Only

Controlled Air-space




That airspace from the surface to 4,000' (unless otherwise designated) above the elevation of selected airports (charted in MSL). The normal radius of the outer limits of Class C airspace is 10NM. Class C airspace is also indicated by the letter C in a box following the airport name.




CLASS D Open Area (White)

Low Chart Only

Controlled Air-space



That airspace from the surface to 2,500' (unless otherwise designated) above the airport elevation (charted in MSL), surrounding those airports that have an operational control tower. Class D airspace is indicated by the letter D in a box following the airport name.



CLASS E Open Area (White)

Low Chart Only

Controlled Air-space

That controlled airspace below 14,500' MSL which is not Class B, C or D.

Federal Airways from 1,200' AGL to but not including 18,000' MSL (unless otherwise specified).

Other designated control areas below 14,500' MSL.

Not Charted

That airspace from 14,500' MSL to but not including 18,000' MSL, including the airspace overlying the waters within 12 NM of the coast of the contiguous United States and Alaska and designated offshore areas, excluding the Alaska peninsula west of longitude 160°00'00" W, and the airspace less than 1,500' AGL.

Airspace Information (Continued)

AIRSPACE - U.S.

CLASS G Screened Brown Area

High and Low Chart

Uncontrolled Airspace




Low Altitude

That portion of the airspace below 14,500' MSL that has not been designated as Class B, C, D or E Airspace.

High Altitude

That portion of the airspace from 18,000' MSL and above that has not been designated as Class A airspace.

Example:




AIRSPACE - CANADIAN

CLASS B Screened Brown Checkered Area


Low Charts Only

Controlled Airspace



Controlled airspace above 12,500' MSL

Example:




AIRSPACE INFORMATION (Continued)


Special Use Airspace - U.S.

Low and High Charts P - Prohibited Area

Example: P-56 - Washington DC, Area A-1 Chart



Example: P-40 and R-4009 - Washington DC, Area A-1 Chart



R - Restricted Area

Example: R3601A -





W - Warning Area

Example: W-50

See Airspace Tabulation on each chart for complete documentation information on:

- Area Identification
- Effective Altitude
- Operating Times
- Controlling Agency Voice Call



Low Charts Only


A - Alert Area



MOA - Military Operations Area

See Airspace Tabulation on each chart for complete documentation information on:

- Area Identification
- Effective Altitude
- Operating Times
- Controlling Agency Voice Call



AIRSPACE INFORMATION (Continued)

Off Route Obstruction Clearance Altitude (OROCA)

Low Charts Only OROCA is computed similarly to the Maximum Elevation Figure (MEF) found on Visual charts except that it provides an additional vertical buffer of 1,000 feet in designated non-mountainous areas and a 2,000 foot vertical buffer in designated mountainous areas within the United States.

Example: 12,500 feet

12⁵

Example: Low L-13 Chart



Special Flight Rules Area (SFRA)

Low and High Charts SFRA Symbolry



Example: Low Chart (Washington Area Chart)




Example: High Chart (H-12)



AIRSPACE INFORMATION (Continued)

Special Use Airspace - Canada & Caribbean

Low and High Charts
 Canada Only
 CYA - Advisory Area



CYD - Danger Area




CYR - Restricted Area



Caribbean Only
 D - Danger Area

In the Caribbean, the first two letters represent the country code, i.e. (MY) Bahamas, (MU) Cuba




NAVIGATIONAL AND PROCEDURAL INFORMATION

Cruising Altitudes - Low Charts - U.S. Only

IFR outside controlled airspace.

IFR within controlled airspace as assigned by ATC.

ALL courses are magnetic.




VFR above 3000' AGL unless otherwise authorized by ATC.

Cruising Altitudes - High Charts - U.S. Only

IFR within controlled airspace as assigned by ATC

All courses are magnetic.


18,000' MSL to FL280



VFR or VFR On Top add 500'


No VFR flights within Class A Airspace above 3000' AGL unless otherwise authorized

RVSM Levels FL290 to FL410



No VFR or VFR On Top authorized above FL285 in RVSM airspace.

FL430 and above



Navigational and Procedural Information (Continued)

ISOGONIC LINE AND VALUE

LOW/HIGH CHARTS

TIME ZONE

All time is Coordinated Universal Time (UTC)

Mountain Std
+7 = UTC

Central Std
+6 = UTC

During periods of Daylights Savings Time (DT), effective hours will be one hour earlier than shown. All states observe DT except Arizona and Hawaii

ENLARGEMENT AREA



MATCH MARK

LOW/HIGH CHARTS



MORSE CODE

A ..	F	K ---	P	U ...	1	6
B	G ---	L	Q ----	V	2	7
C ----	H	M ---	R ---	W ---	3	8
D ---	I ..	N --	S ...	X ---	4	9
E .	J	O ---	T -	Y ----	5	0
				Z ----		

CULTURE

Boundaries

International

LOW/ HIGH ALTITUDE

Date Line

LOW/ HIGH ALTITUDE

--- Omitted when coincident with ARTCC or FIR

..... INTERNATIONAL DATE LINE
..... MONDAY SUNDAY

U.S./Russia Maritime Line

LOW/ HIGH ALTITUDE

RUSSIA
+ + +
UNITED STATES

HYDROGRAPHY


SHORELINES



TOPOGRAPHY

TERRAIN

Area Charts



U.S. TERMINAL PROCEDURES PUBLICATION

The U.S. Terminal Procedure Publications (TPPs) includes the Instrument Approach Procedures (IAPs), Departure Procedures (DPs) charts, Standard Terminal Arrival (STAR) charts, Charted Visual Flight Procedure (CVFP) charts, and Airport Diagrams. Also included are Takeoff Minimums, (Obstacle) Departure Procedures, Diverse Vector Area (RADAR Vectors), RADAR and Alternate Minimum textual procedures.

EXPLANATION OF TPP TERMS AND SYMBOLS

The information and examples in this section are based primarily on the IFR (Instrument Flight Rules) Terminal Procedures Publication (TPP). The publication legends list aeronautical symbols with a brief description of what each symbol depicts. This section will provide more detailed information of some of the symbols and how they are used on TPP charts.

FAA Terminal charts are prepared in accordance with specifications of the Interagency Air Committee (IAC) and their supporting technical groups for the purpose of standardization, which are approved by representatives of the Federal Aviation Administration (FAA), and the Department of Defense (DoD).

The Terminal Procedure Publication is made up of the following charts:


- Instrument Approach Procedure (IAP) Charts
- Airport Diagrams
- Departure Procedures (DP)
- Standard Terminal Arrival (STAR) Charts
- Charted Visual Flight Procedure (CVFP) Charts

INSTRUMENT APPROACH PROCEDURE CHART

The IAPs (charts) are divided into various sections:

Margin Identification Information
 Briefing Strip Information
 Planview
 Missed Approach Information

Profile View
 Landing Minimums
 Airport Sketch



Margin Identification Information

CITY, STATE	AL-0000 (FAA)	00000	RNAV (GPS) RWY 00 AIRPORT NAME (XXX)

VOL, DD MMM YYYY to DD MMM YYYY			VOL, DD MMM YYYY to DD MMM YYYY

CITY, STATE Orig DDMMYY	00°00'N-000°00'W		AIRPORT NAME (XXX) RNAV (GPS) RWY 00

The margin identification at the top, bottom, and sides of the chart provides information about the airport location, procedure identification, and chart currency. The charts are organized by city first, then airport name and state, with the exception of military charts, which are organized by airport name. Going from the top of the chart, reading from left to right, and going down the chart, Margin Identification Information is organized in the following way.

Top Margin Information:

The city and state with which the airport is associated is located on both the top and bottom margins.
 At the center of the top margin is the FAA chart reference number and approving authority in parentheses.

WASHINGTON, DC	AL-5326 (FAA)	15344	RNAV (GPS) RWY 34L MANASSAS RGNL/HARRY P DAVIS FIELD (HEF)				
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">WAAS CH 56239 W34B</td> <td style="width: 20%;">APP CRS 326°</td> <td style="width: 20%;">Rwy Idg TDZE Apt Elev</td> <td style="width: 40%; text-align: right;"> 3715 182 192 </td> </tr> </table>	WAAS CH 56239 W34B	APP CRS 326°	Rwy Idg TDZE Apt Elev	3715 182 192			
WAAS CH 56239 W34B	APP CRS 326°	Rwy Idg TDZE Apt Elev	3715 182 192				

The procedure title is located on both the top and bottom margins. It is derived from the type of navigational facility that is providing the final approach course guidance. The title is abbreviated, e.g. ILS, RNAV, NDB, etc. For airports with parallel runways and simultaneous approach procedures, "L", "R" or "C" follows the runway number to distinguish between left, right, and center runways.

The airport name is shown on both the top and bottom margins below the procedure title. The airport identifier is shown in parentheses following the airport name. Airports outside the contiguous United States will be shown with the FAA designated identifier followed by the ICAO location identifier.

The Date of Latest Revision is shown on the top margin above the procedure title. The Date of Latest Revision identifies the Julian date the chart was last revised for any reason. The first two digits indicate the year, the last three digits indicate the day of the year (001 to 365/6).

WASHINGTON, DC		AL-5326 (FAA)		15344
WAAS CH 56239 W34B	APP CRS 326°	Rwy Idg TDZE Apt Elev	3715 182 192	RNAV (GPS) RWY 34L MANASSAS RGNL/HARRY P DAVIS FIELD (HEF)

15344
Year|Day of Year

Side Margin Information:

The side margins show the volume identification, i.e. SW-3, followed by the current issue date and the next issue date, e.g. SW-3, 21 JUL 2016 to 15 SEP 2016.

Bottom Margin Information:

The FAA Procedure Amendment Number, located on the left bottom margin below the City, State, represents the most current amendment of a given procedure. The Procedure Amendment Effective Date represents the AIRAC cycle date on which the procedure amendment was incorporated into the chart. Updates to the amendment number and effective date represent procedural/criteria revisions to the charted procedure, e.g., course, fix, altitude, minima, etc.

Example: Original Procedure Date

WASHINGTON, DC Orig 10DEC15	MANASSAS RGNL/HARRY P DAVIS FIELD (HEF) 38°43'N-77°31'W	RNAV (GPS) RWY 34L
--------------------------------	--	---------------------------

Example: Amendment Procedure Date

WASHINGTON D.C. Amdt 1B 28MAY15	MANASSAS RGNL/HARRY P DAVIS FIELD (HEF) 38°43'N-77°31'W	RNAV (GPS) RWY 16R
------------------------------------	--	---------------------------

The coordinates for the airport reference point are located at the center of the bottom margin.


BRIEFING STRIP INFORMATION

At the top of every TPP is the Briefing Strip which consists of three stacked strips of information immediately above the planview. Information varies depending upon the type of procedure.

WASHINGTON, DC		AL-443 (FAA)		15288	
LOC/DME I-DCA 111.55 Chan 36		APP CRS 082°		Rwy Idg 6869 TDZE 14 Apt Elev 15	
Top Briefing Strip				ILS or LOC/DME RWY 1 RONALD REAGAN WASHINGTON NATIONAL (DCA)	
Circling NA NE of Rwy 15-33 Night landing Rwy 4 15 NA For inoperative ALSF-2, increase S-LOC T, Cat C and D visibility to 1.0 mile.				ALSF-2 MISSED APPROACH: Climb to 420 then climbing left turn to 2100 on DCA VOR/DME R 325 to GTN NDB/INT/DCA 5.9 DME and hold.	
Middle Briefing Strip					
ATIS 132.65		POTOMAC APP CON 119.85 124.2 269.0 (EAST)		CLNC DEL 128.25	
Communications Briefing Strip					

Top Briefing Strip

The top briefing strip contains procedural information in three separate boxes, in the following sequence from left to right:



- Box 1: Primary Procedure Navigation Information:** The primary navigation type (VOR, LOC, NDB, RNAV, etc.) with its identifier and frequency/channel. If applicable, WAAS, the WAAS Channel Number, and the WAAS Reference Path indicator are shown stacked top to bottom. If the primary navigation type is LAAS, then the following information is shown, stacked top to bottom: LAAS, CH NNNN, RPI XXXX. If there is not a primary Navigation Box required, the first box is removed.
- Box 2: Final Approach Course Information.** The inbound Approach Course (APP CRS) is shown.
- Box 3: Runway Landing Information:** Stacked top to bottom, the runway landing distance (Rwy Ldg), the Touchdown Zone Elevation (TDZE) or Threshold Elevation (THRE), and the Airport Elevation (Apt Elev) are shown. Rwy Ldg may not reflect full runway length due to displaced thresholds and shorter declared distances.

Top Briefing Strip Examples:

Ground based NAVAID:

DENVER, COLORADO				16147	
LOC/DME I-DZG 111.55 Chan 52(Y)	APP CRS 082°	Rwy Idg TDZE Apt Elev	12000 5352 5434	ILS or LOC RWY 7 DENVER INTL (DEN)	

RNAV-WAAS:

DENVER, COLORADO				16147	
WAAS CH 82628 W16B	APP CRS 173°	Rwy Idg TDZE Apt Elev	16000 5326 5434	RNAV (GPS) Y RWY 16R DENVER INTL (DEN)	

LAAS:

NEWARK, NEW JERSEY				16091	
LAAS CH 22727 G04A	APP CRS 039°	Rwy Idg TDZE Apt Elev	8460 10 18	GLS RWY 4L NEWARK LIBERTY INTL (EWR)	

No Primary NAVAID box:

DENVER, COLORADO

16147

APP CRS 173°	Rwy Idg TDZE Apt Elev	12000 5339 5434
------------------------	-----------------------------	--

RNAV (RNP) Z RWY 17L
DENVER INTL (DEN)

Circling Approach:

ROANOKE, VIRGINIA

AL-349 (FAA)

16203

VOR ODR 114.9	APP CRS 236°	Rwy Idg TDZE Apt Elev	N/A N/A 1175
-------------------------	------------------------	-----------------------------	---

VOR/DME-A
ROANOKE-BLACKSBURG RGNL/WOODRUM FIELD (ROA)

Sidestep Procedure:

LOS ANGELES, CALIFORNIA

AL-237 (FAA)

16315

LOC/DME I-OSS 108.5 Chan 22	APP CRS 251°	Rwy Idg TDZE Apt Elev	24R 8925	24L 9483 120 121 126 126
---	------------------------	-----------------------------	--------------------	--

ILS or LOC RWY 24R
LOS ANGELES INTL (LAX)

Middle Briefing Strip

The middle briefing strip may contain information in up to three separate boxes, when available, in the following sequence from left to right:

1

2

3

NOTES BOX	APPROACH LIGHTING SYSTEM	MISSED APPROACH PROCEDURE TEXT BOX
------------------	---------------------------------	---

- **Box 1: Notes Box:** contains procedure notes and Takeoff, Alternate, RADAR, WAAS, and/or Cold Weather indicators (details provided below under Notes Box Symbology)
- **Box 2: Approach Lighting System Box (when applicable):** shows the approach lighting system name and charting icon. Multiple approach lighting systems may be shown for approaches that have straight-in minimums for parallel runways.
- **Box 3: Missed Approach Procedure Text Box:** The full textual description of the missed approach procedure is provided here.

Notes Box Symbology

Several different symbols may appear within the Notes Box:

- ▼ Non-Standard Takeoff minimums and/or Departure Procedures exist. Refer to Takeoff Minimum, (Obstacle) Departure Procedures, and Diverse Vector Area (RADAR VECTORS) section of the TPP
- ▲ Non-standard IFR alternate minimums exist. Refer to IFR Alternate Airport Minimums section of the TPP.
- ▲ NA Alternate minimums are not authorized due to unmonitored facility or absence of weather reporting service.
- W WAAS (Wide Area Augmentation System)
- *-12°C Cold Temperature Restricted Airport

The negative **W** within a black square box symbol shown in the Notes section below any “A” or “T” Symbol indicates that outages of the WAAS (Wide Area Augmentation System) vertical guidance may occur daily at this location due to initial system limitations. WAAS NOTAMs for vertical outages are not provided for this approach. Use LNAV minima for flight planning at these locations, whether as a destination or alternate. For flight operations at these locations, when the WAAS avionics indicate that LNAV/VNAV or LPV service is available, then vertical guidance may be used to complete the approach using the displayed level of service. Should an outage occur during the procedure, reversion to LNAV minima may be required.

When **❄**-12°C appears in the Notes section below all other symbols it indicates a cold temperature altitude correction is required at that airport when the reported temperature is at or below the published restricted temperature. Advise ATC when altitude correction is made in the intermediate and/or missed approach segment. Reporting corrections to ATC in final segment is not required. See Notices to Airmen Publication (NTAP) Graphic Notices General for complete list of published airports, temperature/s, segments and procedure information.

When “ASR”, “PAR” or “ASR/PAR” appear in the Note section immediately below the “T” and “A” symbols it indicates there are published Radar Instrument Approach Minimums. Where radar is approved for approach control service, it is used not only for radar approaches (Airport Surveillance Radar [ASR] and Precision Approach Radar [PAR]) but is also used to provide vectors in conjunction with published non-radar approaches based on radio NAVAIDs (ILS, VOR, NDB, TACAN). Radar vectors can provide course guidance and expedite traffic to the final approach course of any established IAP or to the traffic pattern for a visual approach.

Bottom Briefing Strip (Communications Information)

The communications briefing strip contains communication information when available, in separate boxes, listed from left to right in the order that they would be used during arrival with the tower frequency box bolded:

ATIS XXXXX	APP CON XXXX XXXX	TOWER XXXX XXXX	GND CON XXXXX	CLNC DEL XXXXX	UNICOM XXXXX
----------------------	-----------------------------	----------------------------------	-------------------------	--------------------------	------------------------

- ATIS, AFIS (AK Only) or ASOS/AWOS frequencies (when available, ATIS or AFIS will be the only weather frequency/s published)
- the Approach Control (APP CON) name and frequencies; when the approach service is provided by other than Approach Control, e.g. FSS (Radio), Tower, Center, the appropriate air traffic facility call name is provided.
- the Control Tower (TWR) name and frequencies, to include Precision Radar Monitoring (PRM) and frequency
- Ground Control (GND CON) frequencies
- Clearance Delivery (CLNC DEL) frequencies; where a Control Tower does not exist or is part-time, a remoted CLNC DEL may be listed.
- Controller Pilot Data Link Communication (CPDLC)
- Ground Communications Outlet (GCO) frequency
- Common Traffic Advisory Frequency (CTAF), shown in parentheses when shares a frequency, e.g. UNICOM 122.8 (CTAF)
- UNICOM or AUNICOM frequency

Note: Part-time operations will be annotated with a star. Check Chart Supplement for times of operation.

PLANVIEW


The planview of the IAP charts provides an overhead view of the entire instrument approach procedure.

The data on the planview is shown to scale, unless concentric rings, scale breaks or an inset have been used.

- | | |
|--------------------------------------|--|
| Approach Segments | Hydrography |
| NAVAIDs | International Boundary |
| Restrictive Airspeeds | Obstacles (Man-made, Terrain and Vegetation) |
| Restrictive Altitudes | Special Use Airspace |
| Holding Patterns and Procedure Turns | Minimum Safe Altitude |
| Airports | Terminal Arrival Areas |
| Relief (Terrain Features) | |

Approach Segments


The planview includes a graphical depiction of procedure entry through missed approach.



Sample IAP Example


Legend

- | | | | | |
|---|---|---|---|---|
|  |  |  |  |  |
| Feeder Route | Initial Approach | Intermediate Approach | Final Approach Course | Missed Approach |




Complex IAP Example with RF Legs


- **Feeder Routes** (highlighted in blue - See Simple IAP Example on previous page) may be used to provide a transition from the enroute structure to the IAF.
- **Initial Approach** (highlighted in purple in examples above) is the segment between the initial approach fix (IAF) and the intermediate fix (IF) or the point where the aircraft is established on the intermediate course or final approach course.
- **Intermediate Approach** (highlighted in yellow in examples above) is the segment between the intermediate fix or point and the final approach fix.
- **Final Approach Course** (highlighted in red in the examples above) is the segment between the final approach fix or point and the runway, airport, or missed approach point.
- **Missed Approach** (highlighted in green in the example above) begins at the MAP and continues until the designated fix or waypoint. Missed Approach Procedure Track is shown as a hash marked line in the planview. If the missed approach point falls outside of the area of the planview it will be shown in a separate box in the planview.
- **DME arcs or Radius-to-Fix legs (RF)** are shown as smooth arcs from a designated start point to a designated terminus.



- **Visual Approach Track** is shown on procedures that are authorized to proceed visually such as on procedures that terminate or have missed approaches to the airport.



Traditional (NAVAID) Approach




RNAV Approach

NAVAIDS

NAVAIDS used on ground based charts will show the appropriate symbol accompanied by a data box that contains the facility name, frequency, identifier and Morse code. A NAVAID box with a heavy line indicates the primary NAVAID used for the approach.

NAVAIDS used on GPS based charts show the appropriate symbol identified with the name and identifier.



Restrictive Airspeeds Along the Procedure Track

Restrictive airspeeds along the procedure track are shown paired with their respective fix/facility.

Type	Description	Example
Recommended Speed	Recommended speed is depicted with no lines above or below it	180K
Minimum Speed	Minimum speed is depicted as a number with a line below it	<u>120K</u>
Maximum Speed	Maximum speed is depicted as a number with a line above it	<u>250K</u>
Mandatory Speed	Mandatory speed is depicted as a number with a line above and below it	<u>175K</u>


Altitudes

Restrictive altitudes along the procedure track are shown paired with their respective fix/ facility. Minimum, Maximum, Mandatory and Recommended Altitudes are shown.

Type	Description	Example
Recommended Altitude	Recommended altitude is depicted with no lines above or below it	3000
Minimum Altitude	Minimum altitude is depicted as a number with a line below it	<u>2500</u>
Maximum Altitude	Maximum altitude is depicted as a number with a line above it	<u>4300</u>
Mandatory Altitude	Mandatory altitude is depicted as a number with a line above it	<u>5500</u>
Mandatory Block Altitude	Mandatory block altitude is depicted with a minimum and a maximum altitude.	<u>5000</u> <u>3000</u>


Holding Patterns and Procedure Turns

Holding Patterns are used for many reasons, including deteriorating weather or high traffic volume. Holding might also be required following a missed approach. Each holding pattern has a fix, a direction to hold from the fix, and an airway, bearing, course, radial, or route on which the aircraft is to hold. These elements, along with the direction of the turns, define the holding pattern.




If a holding pattern has a non-standard speed restriction, it will be depicted by an icon with the limiting air speed shown inside the holding pattern symbol. These elements, along with the direction of the turns, define the holding pattern. If two types of holds are located at the same point, the procedural holding pattern will be shown in lieu of arrival or missed approach holding patterns.

A procedure turn is the maneuver prescribed to perform a course reversal to establish the aircraft inbound on an intermediate or final approach course. The procedure turn or hold-in-lieu-of procedure turn is a required maneuver when it is depicted on the approach chart. However, the procedure turn or the hold-in-lieu-of PT is not permitted when the symbol "NoPT" is depicted on the initial segment being flown, when a RADAR VECTOR to the final approach course is provided, or when conducting a timed approach from a holding fix. The procedure turn will be shown in the planview and in the profile of the chart.



Airports

The primary approach airport is shown to scale by a pattern of all the runways. Airports other than the primary approach airport may be shown with an airport pattern and name when in close proximity to the primary airport.




Relief (Terrain Features)

Terrain is depicted in the planview portion of all IAPs at airports that meet the following criteria:

- If the terrain within the planview exceeds 4,000 feet above the airport elevation, or
- If the terrain within a 6.0 nautical mile radius of the Airport Reference Point (ARP) rises to at least 2,000 feet above the airport elevation.

When an airport meets either of the above criteria, terrain will be charted by use of contours, spot elevations, and gradient tints of brown on all IAPs for that airport. Contour layers will be shown in no more than five brown tints, with consecutively darker tints used for consecutively higher elevation contour layers.




Hydrography (Water)

Water Depiction is depicted in grey, in the planview portion of IAPs. See previous example. The following hydrographic features are shown:

- Oceans
- Significant rivers and streams
- Significant lakes - If only one river or one small lake is involved, not located in the immediate airport vicinity, the hydrographic information requirement may be waived.

International Boundary

When the planview includes a boundary of another country the International boundaries are shown by a dashed line. International boundaries are identified with country name within the country area.




Obstacles (Man-made, Terrain and Vegetation)


Obstacles are shown as \triangle when they are man-made or vegetation or as a \bullet when they are terrain. The highest obstacle, whether man-made or terrain is depicted with a bolder and larger symbol along with larger elevation font size. Any obstacle which penetrates a slope of 67:1 emanating from any point along the centerline of any runway shall be considered for charting within the area shown to scale. Obstacles specifically identified by the approving authority for charting shall be charted regardless of the 67:1 requirement.

Unverified obstacles shall be indicated by a doubtful accuracy symbol \pm following the elevation value.


On non-precision approaches, obstacles should be considered when determining where to begin descent from the MDA.



Highest Point - Obstacle



Highest Point - Terrain




Unverified Obstacle - Obstacle

Special Use Airspace (SUA)

SUAs consists of that airspace wherein activities must be confined because of their nature, or wherein limitations are imposed upon aircraft operations that are not a part of those activities, or both. These are prohibited areas, restricted areas, warning areas, Military Operations Areas (MOAs), and alert areas. SUA that falls within the area of coverage of the instrument approach procedure chart are shown only when designated by the approving authority.


Air Defense Identification Zone (ADIZ)

ADIZ is an area of airspace in which the identification, location, and control of aircraft is required in the interest of national security. When designated by the approving authority, ADIZ boundaries that fall within the area of coverage of the chart are shown. CONTIGUOUS U.S. ADIZ




Minimum Safe Altitude (MSA)

MSAs are published for emergency use on IAP charts. MSAs appear in the planview of all IAPs except on approaches for which a Terminal Arrival Area (TAA) is used. The MSA is based on the primary NAVAID, waypoint, or airport reference point on which the IAP is predicated. The MSA depiction on the approach chart contains the identifier of the NAVAID/waypoint/airport used to determine the MSA altitudes. MSAs are expressed in feet above mean sea level and normally have a 25 NM radius; however, this radius may be expanded to 30 NM if necessary to encompass the airport landing surfaces. Ideally, a single sector altitude is established and depicted on the planview of approach charts; however, when necessary to obtain relief from obstructions, the area may be further sectorized and as many as four MSAs established. When established, sectors may be no less than 90° in spread. MSAs provide 1,000 feet clearance over all obstructions but do not necessarily assure acceptable navigation signal coverage.




Terminal Arrival Areas (TAAs)

The TAA icons will be positioned in the planview relative to their relationship to the procedure. The icon will not have feeder routes, airways, or radar vectors depicted. The TAA provides a transition from the enroute structure to the terminal environment with little required pilot/air traffic control interface for aircraft equipped with Area Navigation (RNAV) systems. A standard TAA has three areas: straight-in, left base, and right base. The arc boundaries of the three areas of the TAA are published portions of the approach. A TAA provides minimum altitudes with standard obstacle clearance when operating within the TAA boundaries. TAAs are primarily used on RNAV approaches but may be used on an ILS approach when RNAV is the sole means for navigation to the IF; however, they are not normally used in areas of heavy concentration of air traffic.



Example of Standard TAA

Non-standard TAAs may also be published; i.e., one base leg, no base legs.



Example of Non-Standard TAA

MISSED APPROACH INFORMATION

Missed approach information is shown in 3 locations on the chart:

- The Middle Briefing Strip - The complete textual missed approach instructions are provided at the top of the approach chart in the middle pilot briefing strip.
- The Planview - The missed approach track is drawn using a thin, hash marked line with a directional arrow. If the missed approach point is off the chart, the missed approach track shall extend to the chart border.




- The Profile Box - Missed Approach Icons will be depicted in the upper left or upper right of the profile box. The Missed Approach Icons are intended to provide quick, at a glance intuitive guidance to the pilot, to supplement the textual missed approach instructions in the briefing strip. Space permitting, all textual missed approach instructions will be graphically depicted in sequence. If space does not permit the depiction of all missed approach icons, only the first four icon boxes will be shown.

Example Missed Approach Icons	Missed Approach Text
	MISSED APPROACH: Climb to 13000 on RIL VOR/DME R-250 to TEKGU INT/RIL 19 DME and on EKR VOR/DME R-179 to WOKPA/EKR 44.2 DME and hold, continue climb-in-hold to 13000.
	MISSED APPROACH: Climbing left turn to 8000 via SVC R-128, then reverse course to SVC VOR/DME and hold.
	MISSED APPROACH: Climb to 9000 on track 112° to JETRY, cross JETRY at or above 6700, and on track 112° to PAKPE, right turn to WULKU, and on track 289° to JNC VOR/DME and hold.


Example Missed Approach Icons	Missed Approach Text
	MISSED APPROACH: Climb to 14000 via 174° course to HOMDU and via 160° track to DEVEC and 160° track to FTI VORTAC and hold.
	MISSED APPROACH: Climb to 5800, then climbing left turn to 10000 via heading 190° and SVC VOR/DME R-193 to KUNRE INT/SVC VOR/DME 24.1 DME and hold.

PROFILE VIEW

A profile diagram of the instrument approach procedure is shown below the planview. The published descent profile and graphical depiction of the vertical path using those facilities, intersections, fixes, etc. identified in the procedure to the runway are shown. A profile view of the procedure track is shown. The approach track begins toward the top of the primary facility line, unless otherwise dictated by the procedure, and shall descend to where the final approach ends and the missed approach begins.




RNAV and GLS PROCEDURES WITH VERTICAL GUIDANCE




Precision Approaches

On precision approaches, the glideslope (GS) intercept altitude is illustrated by a zigzag line and an altitude. This is the minimum altitude for GS interception after completion of the procedure turn. Precision approach profiles also depict the GS angle of descent, threshold crossing height (TCH) and GS altitude at the outer marker (OM) or designated fix.




Non-Precision Approaches

On nonprecision approaches, the final segment begins at the Final Approach Fix (FAF) which is identified with the Maltese cross symbol ✖. When no FAF is depicted, the final approach point is the point at which the aircraft is established inbound on the final approach course. Stepdown fixes may also be provided between the FAF and the airport for authorizing a lower minimum descent angle (MDA) and are depicted with the fix or facility name and a dashed line. On RNAV procedures without precision minima i.e., DAs, the approach track descends to the MDA or VDP point, thence horizontally to the missed approach point. On non-RNAV procedures without precision minima, the horizontal segment is shown from the VDP, when it exists, or the MDA when there is no VDP, and a vertical glide angle/TCH is provided.



Visual Descent Point (VDP)

The Visual Descent Point (VDP), is shown by a bold letter "V" positioned above the procedure track and centered on the accompanying dashed line. (See example below.) The VDP is a defined point on the final approach course of a non-precision straight-in approach procedure from which normal descent from the MDA to the runway touchdown point may be commenced.




Visual Flight Path

Instrument approach procedures that terminate or have missed approaches prior to the airport, and are authorized to proceed visual, shall be shown by the dashed line symbol from the missed approach point to the airport. The note “Fly visual” along with the bearing and distance shall be shown leadered to the visual flight path.

RNAV charts sometimes have visual flight for LNAV/VNAV minima which do not start at the missed approach point. An additional note indicating “LNAV/VNAV” will be placed above the note.

Chart Examples



ILS Glide Slope and RNAV Glidepath

A note providing the glide slope (GS) or glidepath (GP) angle and the threshold crossing height (TCH), are positioned in the lower half of the profile box

- GS will be shown on all ILS procedures.
- GP will be shown GLS procedures and all RNAV procedures with a published decision altitude

Threshold Crossing Height (TCH) has been traditionally used in “precision” approaches as the height of the glide slope above threshold. With publication of LNAV/VNAV minimums and RNAV descent angles, including graphically depicted descent profiles, TCH also applies to the height of the “descent angle,” or glidepath, at the threshold.

34:1 Surface Clear Stipple Symbol

On RNAV approach charts, a small shaded arrowhead shaped symbol from the end of the VDA to the runway indicates that the 34:1 Obstacle Clearance Surface (OCS) for the visual segments is clear of obstacles. (See example in VDP Section.)

LANDING MINIMUMS

The landing minimums section is positioned directly below the profile. This section gives the pilot the lowest altitude and visibility requirements for the approach. There are two types of landing minimums: Straight-in landing or Circling. Straight-in landing minimums are the MDA and visibility, or DH and visibility, required for a straight-in landing on a specified runway. Circling minimums are the MDA and visibility required for the circle-to-land maneuver.

The minimums for straight-in and circling are located under each aircraft category. When there is not a division line between minimums for each category, the minimums apply to two or more categories.

LANDING MINIMA FORMAT

In this example airport elevation is 1179, and runway touchdown zone elevation is 1152.

CATEGORY	A	B	C	D
S-ILS 27	1352/24		200	(200-½)
S-LOC 27	1440/24	288	(300-½)	1440/50 288 (300-1)
CIRCLING	1540-1 361 (400-1)	1640-1 461 (500-1)	1640-1½ 461 (500-1½)	1740-2 561 (600-2)

COPTER MINIMA ONLY

CATEGORY	COPTER		
H-176°	680-½	363	(400-½)

No circling minimums are provided

Annotations in diagram:
 - DA: Decision Altitude
 - Visibility (RVR 100's of feet)
 - Aircraft Approach Category HAT/HATh
 - MDA: Minimum Descent Altitude
 - HAA: Height Above Airport
 - Visibility in Statute Miles
 - Copter Approach Direction
 - Height of MDA/DA Above Landing Area (HAL)
 - All weather minimums in parentheses not applicable to Civil Pilots. Military Pilots refer to appropriate regulations.


A second category of straight-in minimums called "sidestep" may be depicted where parallel runways exist.


CATEGORY	A	B	C	D
S-ILS 24R	320/18 200 (200-½)			
S-LOC 24R	460/24	340 (400-½)		460/40 340 (400-¾)
SIDESTEP RWY 24L	580/50	459 (500-1)		580-1½ 459 (500-1½)

The terms used to describe the minimum approach altitudes differ between precision and nonprecision approaches. Precision approaches use DH, which is referenced to the height above threshold elevation (HAT). Nonprecision approaches use MDA, referenced to "feet MSL." The MDA is also referenced to HAT for straight-in approaches, or height above airport (HAA) for circling approaches. The figures listed parenthetically are for military operations and are not used in civil aviation.

The visibility values are shown after the DA/DH or MDA. They are provided in statute miles or runway visual range (RVR). RVR is reported in hundreds of feet. If the visibility is in statute miles, there is an altitude number, hyphen, whole or fractional number, e.g. 530-1. This indicates 530 feet MSL and 1 statute mile of visibility. The RVR value is separated from the minimum altitude with a slash, e.g., 1540/24. This indicates 1540 feet MSL and RVR of 2400 feet.

When a reference mark (*, **, #, etc.) is shown on a line of minimums, the qualifying footnote is provided in the notes section.

FALMOUTH, MASSACHUSETTS		AL-10362 (FAA)		17061	
LOC/DME I-BNX 110.75 Chan 44 (Y)	APP CRS 322°	Rwy Idg TDZE Apt Elev 9501 116 130	ILS or LOC RWY 32 CAPE COD COAST GUARD AIR STATION (F'MH)		
Circling NA northeast of Rwy 14 and northwest of Rwy 23. *RVR 1800 authorized with use of FD or AP or HUD to DA.			MALSR 	MISSED APPROACH: Climb to 1400 then climbing left turn to 2000 on heading 112° and I-BNX localizer SE course to HAGTU INT/I-BNX 6.6 DME and hold.	
ATIS 120.475 236.825	CAPE APP CON * 284.6	COAST GUARD TOWER 128.425	GND CON 124.15 275.8		



Circling Minimums

There was a change to the TERPS criteria in 2012 that affects circling area dimension by expanding the areas to provide improved obstacle protection. To indicate that the new criteria had been applied to a given procedure, a **C** is placed on the circling line of minimums. The new circling tables and explanatory information is located in the Legend of the TPP.

The approaches using standard circling approach areas can be identified by the absence of the **C** on the circling line of minima.

CATEGORY	A	B	C	D
LPV DA	308/24 200 (200-½)			
LNAV/VNAV DA	804-2 696 (700-2)			
LNAV MDA	800/24	692 (700-½)	800-1½	692 (700-1½)
CIRCLING	800-1	687 (700-1)	800-2 687 (700-2)	860-2½ 747 (800-2½)

Apply Standard Circling Approach Maneuvering Radius Table

CATEGORY	A	B	C	D
C CIRCLING	9120-1¼ 1709 (1800-1¼)	9120-1½ 1709 (1800-1½)	9260-3 1849 (1900-3)	NA


Apply Expanded Circling Approach Maneuvering Airspace Radius Table

AIRPORT SKETCH

The airport sketch is a depiction of the airport with emphasis on runway pattern and related information, positioned in either the lower left or lower right corner of the chart to aid pilot recognition of the airport from the air and to provide some information to aid on ground navigation of the airport. The runways are drawn to scale and oriented to true north. Runway dimensions (length and width) are shown for all active runways.

Runway(s) are depicted based on what type and construction of the runway.

Hard Surface	Other Than Hard Surface	Metal Surface	Closed Runway
Under Construction	Stopways, Taxiways, Parking Areas, Water Runways	Displaced Threshold	Closed Taxiway



Taxiways and aprons are shaded grey. Other runway features that may be shown are runway numbers, runway dimensions, runway slope, arresting gear, and displaced threshold.

Other information concerning lighting, final approach bearings, airport beacon, obstacles, control tower, NAVAIDs, helipads may also be shown.

Airport Elevation and Touchdown Zone/Threshold Elevation

The airport elevation is shown enclosed within a box in the upper left corner of the sketch box and the touchdown zone (TDZE) or threshold elevation (THRE) is shown in the upper right corner of the sketch box. The airport elevation is the highest point of an airport's usable runways measured in feet from mean sea level. The touchdown zone is the highest elevation in the first 3,000 feet of the landing surface while the threshold elevation is the elevation of the runway threshold. The chart will show either the TDZE or THRE, except for circling only approaches which will show neither.

Runway Declared Distance Information

Runway declared distance information when available will be indicated by **D** and is shown to the right of the airport elevation in the sketch box. Declared distances for a runway represent the maximum distances available and suitable for meeting takeoff and landing distance performance requirements.


Runway Lights

Notes regarding approach lighting systems are shown at the bottom of the sketch box. Runway lights (HIRL) (MIRL) (LIRL) (TDZL)(TDZ/CL) shall be indicated by a note, e.g. HIRL Rwy 9-27.

Other approach lighting is shown on the airport sketch as a symbol on the side of the runway where they are actually located. Symbols that are shown in negative indicate pilot-controlled lighting.

Runway centerline lights (CL) are installed on some precision approach runways to facilitate landing under adverse visibility conditions. They are located along the runway centerline and are spaced at 50 foot intervals. Runways with CL are shown in a negative dot pattern through the middle of the solid runway as illustrated in the airport sketch to right.

Runway centerline lights will be indicated by a note only when paired with TDZL, e.g., TDZ/CL Rwy 6 and 24.




Time/Distance Table

When applicable, a Time/Distance Table is provided below the airport sketch. The table provides the distance and time that is required from the final approach fix to the missed approach point for select groundspeeds.

AIRPORT DIAGRAMS

Airport Diagrams are specifically designed to assist in the movement of ground traffic at locations with complex runway/taxiway configurations. Airport Diagrams are not intended for use in approach and landing or departure operations. An airport diagram assists pilots in identifying their location on the airport, thus reducing requests for “progressive taxi instructions” from controllers.



Airport Diagram Features:


1. Runways
 - a. complete with magnetic headings (including magnetic variation and epoch year) and identifiers.
 - b. Runways under construction shall also be shown.
 - c. Runway dimensions, displaced thresholds, runway end elevations.
 - d. Runway surface composition
 - e. Weight bearing capacity (landing gear configuration or Pavement Classification Number)
 - f. Land and Hold Short (LAHSO) lines, ILS hold lines, Localizer/Glide Slope Critical Areas.
 - g. Arresting Gear. To include Engineered Materials Arresting System (EMAS).
2. Taxiways, with identifiers. Taxiways under construction shall also be shown.
3. Hot Spot locations.
4. Parking areas, run-up pads, alert areas, landing pads, “Non-Movement” areas (where pilot is NOT under air traffic control), ramps, aprons and hold pads.
5. Turnarounds, blast pads, stopways, overruns, and clearways (include dimensions when known)
6. Large tanks, including fueling area.
7. Control towers (include tower height).
8. Airport beacon.
9. Helicopter pads.
10. Radar reflectors.
11. Highest obstruction within diagram boundary.
12. Any building that pilot can taxi to. Other buildings to include terminal/administration and Base operations, fire station, NWS, AFSS, FAA, FSDO, ANG, USCG, FBO.
13. Comm Frequencies.

Note: Star when used in the Comm Frequencies indicates part-time status. Check Chart Supplement for times of operation.

10210

AIRPORT DIAGRAM

ASSOCIATED CITY/AIRPORT NAME (AAA)
AL-9999 (FAA)
ASSOCIATED CITY, STATE



AIRPORT DIAGRAM

ASSOCIATED CITY/AIRPORT NAME (AAA)
ASSOCIATED CITY, STATE

10210

Runway Construction

Runway construction is depicted as follows:

Hard Surface	Other Than Hard Surface	Metal Surface	Closed Runway	Closed Taxiway	Under Construction	Stopways, Taxiways, Parking Areas, Water Runways	Displaced Threshold

Hot Spots

Hot Spots are a runway safety related problem area or intersection on an airport. Typically it is a complex or confusing taxiway/taxiway or taxiway/runway intersection. A confusing condition may be compounded by a miscommunication between a controller and a pilot, and may cause an aircraft separation standard to be compromised. The area may have a history of surface incidents or the potential for surface incidents.

Hot Spots are indicated on the Airport Diagram with a brown open circle or polygon leadered to a Hot Spot number, e.g., HS 1. The number corresponds to a listing and description on the Hot Spot page in the front the TPP. More information and location of Hot Spots can be found at http://www.faa.gov/airports/runway_safety/hotspots/hotspots_list/.

DEPARTURE PROCEDURES (DPs)

Departure Procedures (DPs) are designed specifically to assist pilots in avoiding obstacles during the climb to the minimum enroute altitude, and/or airports that have civil IFR takeoff minimums other than standard. There are two types of DPs: Obstacle Departure Procedures (ODPs), printed either textually or graphically and Standard Instrument Departures (SIDs), always printed graphically. SIDs are primarily designed for system enhancement and to reduce pilot/controller workload, and require ATC clearance. ODPs provide obstruction clearance via the least onerous route from the terminal area and may be flown without ATC clearance. All DPs provide the pilot with a safe departure from the airport and transition to the enroute structure.

Generally, DP charts are depicted “not to scale” due to the great distances involved on some procedures or route segments. A “to scale” portrayal may be used if readability is assured.

The DP will show the departure routing, including transitions to the appropriate enroute structure. All routes, turns, altitudes, NAVAIDs, facilities forming intersections and fixes, and those facilities terminating the departure route are shown. A textual description of the departure procedure is also provided. For RNAV DPs, the transition text consists of the transition name and associated computer code. On non-RNAV DPs, the transition text will also include the description of all turns, altitudes, radials, bearings and facilities/fixes needed to guide the user from the common departure point to the terminating facility fix.

STANDARD TERMINAL ARRIVAL (STARs) CHARTS

STARs are pre-planned Instrument Flight Rule (IFR) air traffic control arrival procedures for pilot use in graphic and/or textual form. STARs depict prescribed routes to transition the aircraft from the enroute structure to a fix in the terminal area from which an instrument approach can be conducted. STARs reduce pilot/controller workload and air-ground communications, minimizing error potential in delivery and receipt of clearances.

STAR charts generally shall be depicted ‘not to scale’ due to the great distances involved on many procedures and route segments. A ‘to scale’ depiction may be used only if readability is assured.

The STAR will show the arrival routing, including transitions from the appropriate enroute structure. All routes, turns, altitudes, NAVAIDs, facilities forming intersections and fixes, and those facilities/fixes terminating or beginning the arrival route shall be shown in the graphic depiction. A textual description of the arrival procedure is also provided. For RNAV STARs, transition text will consist of the transition name and associated computer code. For non-RNAV STARs, the transition text will also include a description of all turns, altitudes, radials, bearings and facilities/fixes needed to guide the user from the entry point to the common facility/fix.

CHARTED VISUAL FLIGHT PROCEDURE (CVFP) CHARTS

CVFPs are charted visual approaches established for environmental/noise considerations, and/or when necessary for the safety and efficiency of air traffic operations. The approach charts depict prominent landmarks, courses, and recommended altitudes to specific runways. CVFPs are designed to be used primarily for turbojet aircraft. CVFPs are not instrument approaches and do not have missed approach segments.

CVFPs are named for the primary landmark and the specific runway for which the procedure is developed, such as: RIVER VISUAL RWY 18, STADIUM VISUAL RWY 24. The CVFP charts are divided into planview and notes sections separated by a bar scale in 1 NM increments. The planview of the CVFP includes the portrayal of visual approach procedures information, such as landmarks, NAVAIDs, visual track, hydrography, special use airspace and cultural features, as applicable.

CVFPs originate at or near, and are designed around, prominent visual landmarks and typically do not extend beyond 15 flight path miles from the landing runway. Visual tracks start at a geographical point or landmark where the procedure must be flown visually to the airport. The visual track is indicated by a dashed line. Visual tracks may include the track value, distance and minimum or recommended altitudes.

U.S. TERMINAL PROCEDURES PUBLICATION SYMBOLS

GENERAL INFORMATION

Symbols shown are for the Terminal Procedures Publication (TPP) which includes Standard Terminal Arrival (STARs) Charts, Departure Procedures (DPs), Instrument Approach Procedures (IAP) and Airport Diagrams.

LEGEND - STANDARD TERMINAL ARRIVAL (STAR) CHARTS - DEPARTURE PROCEDURE (DP) CHARTS

LEGEND 17229

LEGEND

STANDARD TERMINAL ARRIVAL (STAR) CHARTS

DEPARTURE PROCEDURE (DP) CHARTS

Applies to both STAR and DP Charts unless otherwise noted.

<h4>RADIO AIDS TO NAVIGATION</h4> <p>Compulsory:</p> <p> VOR VORTAC DME NDB/DME VOR/DME TACAN NDB </p> <p>Non-Compulsory:</p> <p> VOR VORTAC DME VOR/DME TACAN NDB NDB/DME </p> <p> LMM, LOM (Compass locator) Marker Beacon </p> <p> LOC LOC/DME (shown when installation is offset from its normal position off the end of the runway.) (DP) </p> <p> Localizer Course SDF Course </p>	<h4>ROUTES</h4> <p> 4500 MEA-Minimum Enroute Altitude *3500 MOCA-Minimum Obstruction Clearance Altitude 270° Departure Route - Arrival Route (65) Mileage between Radio Aids, Reporting Points, and Route Breaks </p> <p> Transition Route R-275 Radial line and value Lost Communications Track V12 Airway/Jet Route Identification J80 Airway/Jet Route Identification DP Holding Pattern STAR Holding Pattern (IAS) Holding pattern with max. restricted airspeed (175K) applies to all altitudes (210K) applies to altitudes above 6000' and including 14000' </p>
<p>(T) indicates frequency protection range (STAR)</p> <p> Identifier: ORLANDO Frequency: 112.25 (T) Chan 59 (Y) Geographic Position: N28°32.56' W81°20.10' Underline indicates no voice transmitted on this frequency L-19, H-5 Enroute Chart Reference DME or TACAN Channel </p> <p> Coordinates: N38°58.30' W89°51.50' Frequency: 112.7 CAP Identifier: PRAYS Waypoint Name Radial-Distance (Facility to Waypoint): 590 Reference Facility Elevation </p>	<h4>SPECIAL USE AIRSPACE</h4> <p> R-352 R-Restricted W-Warning P-Prohibited A-Alert MOA-Military Operations Area </p> <h4>ALTITUDES</h4> <p> 5500 Mandatory Altitude (Cross at) 2300 Minimum Altitude (Cross at or above) 4800 Maximum Altitude (Cross at or below) </p> <p> 15000 Block Altitude 12000 Altitude change at other than Radio Aids (STAR) </p> <h4>INDICATED AIRSPEED</h4> <p> 175K Mandatory Airspeed 120K Minimum Airspeed 250K Maximum Airspeed </p>
<h4>FIXES/ATC REPORTING REQUIREMENTS</h4> <p> Reporting Points: N00°00.00' W00°00.00' (75) DME Mileage (when not obvious) </p> <p> ▲ Fix-Compulsory and △ Non-Compulsory Position Report </p> <p> DME fix WAYPOINT (Compulsory) WAYPOINT (Non-Compulsory) </p> <p> FLYOVER POINT X Computer Navigation Fix (CNF) N00°00.00' W00°00.00' </p>	<h4>AIRPORTS</h4> <p> (DP) Joint Civil Military Civil-Military Airports not served by the procedure shown in screened color (STAR) </p> <p> Civil Military Joint Civil-Military </p> <h4>MISCELLANEOUS</h4> <p> Changeover Point Distance not to scale (DP) International Boundary (DP) Air Defense Identification Zone Takeoff Minimums and (Obstacle) Departure Procedures entry published. (DP) </p>

12 OCT 2017 to 09 NOV 2017

12 OCT 2017 to 09 NOV 2017

LEGEND 17229

APPROACH LIGHTING SYSTEM

LEGEND 15344

INSTRUMENT APPROACH PROCEDURES (CHARTS)
APPROACH LIGHTING SYSTEM - UNITED STATES

<p>Approach lighting and visual glide slope systems are indicated on the airport sketch by an identifier, e.g., (A2), (V), etc.</p> <p>A dot "•" portrayed with approach lighting letter identifier indicates sequenced flashing lights (F) installed with the approach lighting system e.g., (A1). Negative symbology, e.g., (A4), (V) indicates Pilot Controlled Lighting (PCL).</p>		
<p>RUNWAY TOUCHDOWN ZONE AND CENTERLINE LIGHTING SYSTEMS</p> <p>TDZ/CL</p> <p>TDZL</p> <p>CL</p> <p>RUNWAY CENTERLINE LIGHTS</p> <p>AVAILABILITY of TDZ/CL will be shown by NOTE in SKETCH e.g. "TDZ/CL Rwy 15"</p>	<p>SHORT APPROACH LIGHTING SYSTEM</p> <p>(A2)</p> <p>SALS/SALSF (High Intensity)</p> <p>SAME AS INNER 1500' OF ALSF-1</p>	<p>OMNIDIRECTIONAL APPROACH LIGHTING SYSTEM</p> <p>(A3)</p> <p>ODALS</p> <p>THRESHOLD</p> <p>1500'</p> <p>SEQUENCED FLASHING LIGHTS</p> <p>LENGTH 1500 FEET</p>
	<p>APPROACH LIGHTING SYSTEM</p> <p>(A1)</p> <p>ALSF-2</p> <p>500'</p> <p>1000'</p> <p>2400'/3000'</p> <p>GREEN</p> <p>WHITE</p> <p>RED</p> <p>SEQUENCED FLASHING LIGHTS</p> <p>NOTE: CIVIL ALSF-2 MAY BE OPERATED AS SSALR DURING FAVORABLE WEATHER CONDITIONS</p> <p>(High Intensity)</p> <p>LENGTH 2400/3000 FEET</p>	<p>SIMPLIFIED SHORT APPROACH LIGHTING SYSTEM</p> <p>with Runway Alignment Indicator Lights</p> <p>(A5)</p> <p>SSALR</p> <p>1000'</p> <p>2400'/3000'</p> <p>GREEN</p> <p>WHITE</p> <p>SEQUENCED FLASHING LIGHTS</p> <p>(High Intensity)</p> <p>LENGTH 2400/3000 FEET</p>
<p>APPROACH LIGHTING SYSTEM</p> <p>(A4)</p> <p>ALSF-1</p> <p>1000'</p> <p>2400'/3000'</p> <p>GREEN</p> <p>RED</p> <p>WHITE</p> <p>SEQUENCED FLASHING LIGHTS</p> <p>(High Intensity)</p> <p>LENGTH 2400/3000 FEET</p>	<p>MEDIUM INTENSITY (MALS and MALSF) OR SIMPLIFIED SHORT (SSALS and SSALF) APPROACH LIGHTING SYSTEMS</p> <p>(A2)</p> <p>1000'</p> <p>1400'</p> <p>400'</p> <p>GREEN</p> <p>WHITE</p> <p>SEQUENCED FLASHING LIGHTS FOR MALS/SSALF ONLY</p> <p>LENGTH 1400 FEET</p>	<p>(V)</p> <p>VISUAL APPROACH SLOPE INDICATOR</p> <p>VASI</p> <p>3-BAR, 6 OR 16 BOX, VISUAL APPROACH SLOPE INDICATOR THAT PROVIDES 2 GLIDE ANGLES AND 2 THRESHOLD CROSSING HEIGHTS.</p> <p>VASI 6</p> <p>VASI 16</p> <p>THRESHOLD</p> <p>THRESHOLD</p>
<p>APPROACH LIGHTING SYSTEM</p> <p>(A5)</p> <p>MALS</p> <p>1000'</p> <p>3000'</p> <p>GREEN</p> <p>WHITE</p> <p>SEQUENCED FLASHING LIGHTS</p> <p>(High Intensity)</p> <p>LENGTH 2400/3000 FEET</p>	<p>MEDIUM INTENSITY APPROACH LIGHTING SYSTEM</p> <p>with Runway Alignment Indicator Lights</p> <p>(A5)</p> <p>MALS</p> <p>SAME LIGHT CONFIGURATION AS SSALR.</p>	<p>(V)</p> <p>VISUAL APPROACH SLOPE INDICATOR</p> <p>VASI</p> <p>3-BAR, 6 OR 16 BOX, VISUAL APPROACH SLOPE INDICATOR THAT PROVIDES 2 GLIDE ANGLES AND 2 THRESHOLD CROSSING HEIGHTS.</p> <p>VASI 6</p> <p>VASI 16</p> <p>THRESHOLD</p> <p>THRESHOLD</p>

12 OCT 2017 to 09 NOV 2017

12 OCT 2017 to 09 NOV 2017

LEGEND 15344

APPROACH LIGHTING SYSTEM (Continued)

LEGEND 04330

INSTRUMENT APPROACH PROCEDURES (CHARTS) APPROACH LIGHTING SYSTEM - UNITED STATES

Approach lighting and visual glide slope systems are indicated on the airport sketch by an identifier, (A₂), (V) etc.

A dot "•" portrayed with approach lighting letter identifier indicates sequenced flashing lights (F) installed with the approach lighting system e.g., (A₁). Negative symbology, e.g., (A₁), (V) indicates Pilot Controlled Lighting (PCL).

(P) **PRECISION APPROACH PATH INDICATOR**
PAPI

Legend: □ White ■ Red

(V₂) **PULSATING VISUAL APPROACH SLOPE INDICATOR**
PVASI

CAUTION: When viewing the pulsating visual approach slope indicators in the pulsating white or pulsating red sectors, it is possible to mistake this lighting aid for another aircraft or a ground vehicle. Pilots should exercise caution when using this type of system.

(V₁) **"T"-VISUAL APPROACH SLOPE INDICATOR**
"T"-VASI

"T" ON BOTH SIDES OF RWY
ALL LIGHTS VARIABLE WHITE.
CORRECT APPROACH SLOPE-
ONLY CROSS BAR VISIBLE.
UPRIGHT "T"- FLY UP.
INVERTED "T"- FLY DOWN.
RED "T"- GROSS
UNDERSHOOT.

(V₄) **TRI-COLOR VISUAL APPROACH SLOPE INDICATOR**
TRCV

CAUTION: When the aircraft descends from green to red, the pilot may see a dark amber color during the transition from green to red.

12 OCT 2017 to 09 NOV 2017

12 OCT 2017 to 09 NOV 2017

(V₅) **ALIGNMENT OF ELEMENTS SYSTEMS**
APAP

Painted panels which may be lighted at night.
To use the system the pilot positions the aircraft
so the elements are in alignment.

LEGEND 04330

AIRPORT DIAGRAM/AIRPORT SKETCH

LEGEND 16147

INSTRUMENT APPROACH PROCEDURES (CHARTS)

AIRPORT DIAGRAM/AIRPORT SKETCH

Runways

Hard Surface	Other Than Hard Surface	Stopways, Taxiways, Parking Areas, Water Runways	Displaced Threshold

ARRESTING GEAR: Specific arresting gear systems; e.g., BAK12, MA-1A etc., shown on airport diagrams, not applicable to Civil Pilots. Military Pilots refer to appropriate DOD publications.

Closed Runway	Closed Taxiway	Under Construction	Metal Surface

uni-directional bi-directional Jet Barrier

ARRESTING SYSTEM (EMAS)

REFERENCE FEATURES

Hot Spot	
Runway Holding Position Markings	
Buildings	
24-Hour Self-Serve Fuel ##	
Tanks	
Obstructions	
Airport Beacon #	
Runway	
Radar Reflectors	
Control Tower #	

When Control Tower and Rotating Beacon are co-located, Beacon symbol will be used and further identified as TWR.

A fuel symbol is shown to indicate 24-hour self-serve fuel available, see appropriate Chart Supplement for information.

Runway length depicted is the physical length of the runway (end-to-end, including displaced thresholds if any) but excluding areas designated as stopways.

A symbol is shown to indicate runway declared distance information available, see appropriate Chart Supplement for distance information.

Runway Weight Bearing Capacity/or PCN Pavement Classification Number is shown as a codified expression. Refer to the appropriate Supplement/Directory for applicable codes e.g., RWY 14-32 PCN 80 F/D/X/U S-75, D-185, 2S-175, 2D-325

SCOPE

Airport diagrams are specifically designed to assist in the movement of ground traffic at locations with complex runway/taxiway configurations. Airport diagrams are not intended to be used for approach and landing or departure operations. For revisions to Airport Diagrams: Consult FAA Order 7910.4.

Helicopter Alighting Areas

Negative Symbols used to identify Copter Procedures landing point

Runway Threshold elevation.....THRE 123
Runway TDZ elevation.....TDZE 123

Runway Slope.....0.3% DOWN
Runway Slope.....0.8% UP
(shown when runway slope is greater than or equal to 0.3%)

NOTE:
Runway Slope measured to midpoint on runways 8000 feet or longer.

U.S. Navy Optical Landing System (OLS) "OLS" location is shown because of its height of approximately 7 feet and proximity to edge of runway may create an obstruction for some types of aircraft.

Approach light symbols are shown in the Flight Information Handbook.

Airport diagram scales are variable.

True/magnetic North orientation may vary from diagram to diagram

Coordinate values are shown in 1 or 1/2 minute increments. They are further broken down into 6 second ticks, within each 1 minute increments.

Positional accuracy within ±600 feet unless otherwise noted on the chart.

NOTE:
All new and revised airport diagrams are shown referenced to the World Geodetic System (WGS) (noted on appropriate diagram), and may not be compatible with local coordinates published in FLIP. (Foreign Only)

12 OCT 2017 to 09 NOV 2017

12 OCT 2017 to 09 NOV 2017

LEGEND 16147

PLANVIEW SYMBOLS

LEGEND 17229

INSTRUMENT APPROACH PROCEDURES (CHARTS)

PLANVIEW SYMBOLS

TERMINAL ROUTES

HOLDING PATTERNS

Holding pattern with max. restricted airspeed:
 (175K) applies to all altitudes.
 (210K) applies to altitudes above 6000' to and including 14000'.
 Arrival Holding Pattern altitude restrictions will be indicated when they deviate from the adjacent leg.
 Limits will only be specified when they deviate from the standard. DME fixes may be shown.

FIXES/ATC REPORTING REQUIREMENTS

Reporting Point
 ▲ Name (Compulsory) ✕ Intersection
 △ Name (Non-Compulsory)

◆ WAYPOINT (Compulsory) ✧ WAYPOINT (Non-Compulsory)

⊙ FLYOVER POINT ⊕ MAP WP (Flyover)

Computer Navigation Fix (CNF)
 x (NAME) ("x" omitted when it conflicts with runway pattern)

15 DME Distance From Facility AUSTN INT ARC/DME/RNAV Fix

R-198 Radial line and value
 LR-198 Lead Radial
 LB-198 Lead Bearing

ALTITUDES

5500 Mandatory Altitude 3000 Recommended Altitude
 2500 Minimum Altitude 5000 Mandatory Block
 4300 Maximum Altitude 3000 Altitude

INDICATED AIRSPEED

175K	120K	250K	180K
Mandatory Airspeed	Minimum Airspeed	Maximum Airspeed	Recommended Airspeed

RADIO AIDS TO NAVIGATION

110.1 Underline indicates No Voice transmitted on this frequency

Compulsory:
 ● VOR ● VORTAC ■ DME
 ■ VOR/DME ● TACAN ● NDB ● NDB/DME

Non-Compulsory:
 ○ VOR ○ VORTAC □ DME
 □ VOR/DME ○ TACAN ○ NDB □ NDB/DME

◉ LOM/LMM (Compass locator at Outer Marker/Middle Marker)
 Marker Beacon
 Marker beacons that are not specifically part of the procedure but underlie the final approach course are shown in screened color.

▬ Localizer (LOC/LDA) Course
 Right side shading- Front course; Left side shading- Back Course

▬ SDF Course

☑ LOC/DME
 ⊙ LOC/LDA/SDF Transmitter (shown when installation is offset from its normal position off the end of the runway.)

Waypoint Data

Coordinates	PRAYS	Waypoint Name
Frequency	N38° 58.30' W89° 51.50'	
Identifier	112.7 CAP	Radial-Distance (Facility to Waypoint)
	590	Reference Facility Elevation

Primary Navaid with Coordinate Values

LIMA	
114.5 LIM	
Chan 92	
S12° 00.80'	
W77° 07.00'	

Secondary Navaid

LMM	
LIMA	
248 NT	

SCOTT Chan 59 VHF Paired Frequency (112.2)


12 OCT 2017 to 09 NOV 2017

12 OCT 2017 to 09 NOV 2017

LEGEND 17229

PLANVIEW SYMBOLS (Continued)

LEGEND 15232 INSTRUMENT APPROACH PROCEDURES (CHARTS)



12 OCT 2017 to 09 NOV 2017

12 OCT 2017 to 09 NOV 2017





LEGEND 15232

PROFILE VIEW

LEGEND 17229 INSTRUMENT APPROACH PROCEDURES (CHARTS)

PROFILE VIEW

- Three different methods are used to depict either electronic or vertical guidance: "GS", "GP", or "VDA".
- "GS" indicates that an Instrument Landing System (ILS) electronic glide slope (a ground antenna) provides vertical guidance. The profile section of ILS procedures depict a GS angle and TCH in the following format: $\text{GS } 3.00^\circ$.
TCH 55
 - "GP" on GLS and RNAV procedures indicates that either electronic vertical guidance (via Wide Area Augmentation System - WAAS or Ground Based Augmentation System - GBAS) or barometric vertical guidance is provided. GLS and RNAV procedures with a published decision altitude (DA/H) depict a GP angle and TCH in the following format: $\text{GP } 3.00^\circ$.
TCH 50
 - An advisory vertical descent angle (VDA) is provided on non-vertically guided conventional procedures and RNAV procedures with only a minimum descent altitude (MDA) to assist in preventing controlled flight into terrain. On Civil (FAA) procedures, this information is placed above or below the procedure track following the fix it is based on. Absence of a VDA or a note that the VDA is not authorized indicates that the prescribed obstacle clearance surface is not clear and the VDA must not be used below MDA. VDA is depicted in the following format: $\leq 3.00^\circ$.
TCH 55



ALTITUDES		PROFILE SYMBOLS	
<u>5500</u> Mandatory Altitude	3000 Recommended Altitude	$\frac{2400}{\text{---}}$ Glide Slope/Glidepath Intercept Altitude and final approach fix for vertically guided approach procedures.	--- Visual Flight Path
<u>2500</u> Minimum Altitude	<u>5000</u> Mandatory Block Altitude	∇ Visual Descent Point (VDP)	--- Note: Facilities and waypoints are depicted as a solid vertical line while fixes and intersections are depicted as a dashed vertical line.
<u>4300</u> Maximum Altitude	<u>3000</u> Altitude		


12 OCT 2017 to 09 NOV 2017

12 OCT 2017 to 09 NOV 2017

LEGEND 17229

COLD TEMPERATURE AIRPORTS

COLD TEMPERATURE RESTRICTED AIRPORTS








NOTE: A -12°C symbol indicates a cold temperature altitude correction is required at this airport when reported temperature is at or below the published restricted temperature. Pilots familiar with cold temperature procedure in the Notice to Airman Publication (NTAP) and correcting all altitudes from the IAF to the MA final holding altitude do not have to reference the NTAP. Pilots wishing to correct on individual segments must reference the NTAP airport list for affected segments. See Notice to Airman Publication (NTAP) Graphic Notices General for complete list of published airports, temperature, segments, and procedure information. www.faa.gov/air_traffic/publications/notices. Pilots will advise ATC with the required altitude correction when making a correction to any segment other than the final segment. See following Cold Temperature Error Table to make manual corrections.

COLD TEMPERATURE ERROR TABLE
HEIGHT ABOVE AIRPORT IN FEET

	200	300	400	500	600	700	800	900	1000	1500	2000	3000	4000	5000	
REPORTED TEMP °C	+10	10	10	10	10	20	20	20	20	20	30	40	60	80	90
0	20	20	30	30	40	40	50	50	60	90	120	170	230	280	
-10	20	30	40	50	60	70	80	90	100	150	200	290	390	490	
-20	30	50	60	70	90	100	120	130	140	210	280	420	570	710	
-30	40	60	80	100	120	140	150	170	190	280	380	570	760	950	
-40	50	80	100	120	150	170	190	220	240	360	480	720	970	1210	
-50	60	90	120	150	180	210	240	270	300	450	590	890	1190	1500	

REFERENCES

There are several references available from the FAA to aid pilots and other interest parties to learn more about FAA Charts and other aspects of aviation.

Publication		FAA Publication ID
	<p>Aeronautical Information Manual (AIM)</p> <p>URL: http://www.faa.gov/air_traffic/publications/</p>	
	<p>Airplane Flying Handbook</p> <p>URL: http://www.faa.gov/regulations_policies/handbooks_manuals/aircraft/airplane_handbook/</p>	FAA-H-8083-3A
	<p>Helicopter Flying Handbook</p> <p>URL: http://www.faa.gov/regulations_policies/handbooks_manuals/aviation/helicopter_flying_handbook/</p>	FAA-H-8083-21A
	<p>Instrument Procedures Handbook</p> <p>URL: http://www.faa.gov/regulations_policies/handbooks_manuals/aviation/instrument_procedures_handbook/</p>	FAA-H-8083-16B
	<p>Instrument Flying Handbook</p> <p>URL: http://www.faa.gov/regulations_policies/handbooks_manuals/aviation/media/FAA-H-8083-15B.pdf</p>	FAA-H-8083-15B
	<p>Pilot's Handbook of Aeronautical Knowledge</p> <p>URL: http://www.faa.gov/regulations_policies/handbooks_manuals/aviation/media/pilot_handbook.pdf</p>	FAA-H-8083-25B
	<p>Remote Pilot - Small Unmanned Aircraft Systems Study Guide</p> <p>URL: http://www.faa.gov/regulations_policies/handbooks_manuals/aviation/media/remote_pilot_study_guide.pdf</p>	FAA-G-8082-22

ABBREVIATIONS

A

AAS - Airport Advisory Service
AAUP - Attention All Users Page
ADF - Automatic Direction Finder
ADIZ - Air Defense Identification Zone
ADS - Automatic Dependent Surveillance
ADS-B - Automatic Dependent Surveillance-Broadcast
Advstry - Advisory
AFIS - Automatic Flight Information Service
AFS - Air Force Station
AGL - Above Ground Level
AIM - Aeronautical Information Manual
AIRAC - Aeronautical Information Regulation And Control
APP - Approach
Apt - Airport
APV - Approaches with Vertical Guidance
ARP - Airport Reference Point
ARTCC - Air Route Traffic Control Center
ASDA - Accelerate-Stop Distance Available
ASDE-X - Airport Surface Detection Equipment-Model X
ASOS - Automated Surface Observing Station
ASR - Airport Surveillance Radar
ATC - Air Traffic Control
ATIS - Automatic Terminal Information Service
ATS - Air Traffic Service
AUNICOM - Automated Aeronautical Advisory Station
AWOS - Automated Weather Observing Station

B

Baro-VNAV - Barometric Vertical Navigation
BS - Broadcast Station

C

CAC - Caribbean Aeronautical Chart
CAT - Category
CFA - Controlled Firing Areas
CFR - Code of Federal Regulations
CLNC DEL - Clearance Delivery
CH - Channel
CNF - Computer Navigation Fix
COP - Changeover Point
CPDLC - Controller Pilot Data Link Communication
CRS - Course
CT - Control Tower
CTAF - Common Traffic Advisory Frequency
CVFP - Charted Visual Flight Procedure

D

DA - Decision Altitude
DA - Density Altitude
D-ATIS - Digital Automatic Terminal Information Service
DH - Decision Height
DoD - Department of Defense

DME - Distance Measuring Equipment
DP - Departure Procedure
DT - Daylight Savings Time
DVA - Diverse Vector Area

E

E - East
EFAS - Enroute Flight Advisory Service
EFB - Electronic Flight Bag
Elev - Elevation

F

FAA - Federal Aviation Administration
FAF - Final Approach Fix
FAP - Final Approach Point
FAR - Federal Aviation Regulation
FIR - Flight Information Region
FL - Flight Level
FLIP - Flight Information Publication
FMS - Flight Management System
FREQ - Frequency
FRZ - Flight Restricted Zone
FSDO - Flight Standards District Office
FSS - Flight Service Station

G

GBAS - Ground-Based Augmentation System
GCO - Ground Communications Outlet
GLS - GBAS Landing System
GND - Ground
GNSS - Global Navigation Satellite System
GPS - Global Positioning System
GS - Ground Speed

H

HAA - Height Above Airport
HAR - High Altitude Redesign
HAT - Height Above Touchdown
HF - High Frequency
HIWAS - Hazardous Inflight Weather Advisory Service

I

IAC - Interagency Air Committee
IACC - Interagency Air Cartographic Committee
IAF - Initial Approach Fix
IAP - Instrument Approach Procedure
ICAO - International Civil Aviation Authority
IDT - Identifier
IF - Intermediate Fix
IFR - Instrument Flight Rules
ILS - Instrument Landing System
IMC - Instrument Meteorological Conditions

INS - Inertial Navigation System
IR - Instrument Route
IRU - Inertial Reference Unit

K

KIAS - Knots

L

LAAS - Local Area Augmentation System
LAHSO - Land and Hold Short
LAA - Local Airport Advisory
LAAS - Local Area Augmentation System
LDA - Localizer-type Directional Aid
LDA - Landing Distance Available
Ldg - Landing
LF - Low Frequency
LNAV - Lateral Navigation
LOC - Localizer
LOM - Locator Outer Marker
LPV - Localizer Performance with Vertical Guidance
LRRS - Long Range Radar Station
LTP - Landing Threshold Point

M

MAA - Maximum Authorized Altitude
MAP - Missed Approach Point
MCA - Minimum Crossing Altitude
MDA - Minimum Descent Altitude
MDH - Minimum Descent Height
MEA - Minimum Enroute Altitude
MEF - Maximum Elevation Figure
MF - Medium Frequency
MIA - Minimum IFR Altitude
MOA - Military Operations Areas
MOCA - Minimum Obstruction Clearance Altitude
MORA - Minimum Off-Route Altitude
MRA - Minimum Reception Altitude
MSA - Minimum Safe Altitude
MSL - Mean Sea Level
MTA - Minimum Turning Altitude
MTR - Military Training Route
MVA - Minimum Vector Altitude

N

N - North
N/A - Not Applicable
NA - Not Authorized
NAS - National Airspace System
NAVAID - Navigational Aid (Ground based)
NDB - Non-Directional Radiobeacon
NextGen - Next Generation Air Transportation System
NFDC - National Flight Data Center
NFPO - National Flight Procedures Office
NM - Nautical Mile
NOAA - National Oceanic and Atmospheric Administration

NO A/G - No Air-to-Ground Communication
NOTAM - Notice to Airman
NoPT - No Procedure Turn
NPA - Non-Precision Approach
NTAP - Notices to Airman Publication
NWS - National Weather Service

O

OAT - Outside Air Temperature
OBS - Omni Bearing Selector
OCA - Ocean Control Area
OCS - Obstacle Clearance Surface
ODP - Obstacle Departure Procedure
OROCA - Off Route Obstruction Clearance Altitude

P

PA - Precision Approach
PAR - Precision Approach Radar
PRM - Precision Runway Monitor
PT - Procedure Turn
PTP - Point-to-Point
Pvt - Private

R

R - Radial
R - Receive
R - Restricted Area (Special Use Airspace)
RCO - Remote Communications Outlet
RF - Radius-to-Fix
RNAV - Area Navigation
RNP - Required Navigation Performance
RNP AR - Required Navigation Performance Authorization
Required
ROC - Required Obstacle Clearance
RVR - Runway Visual Range
RVSM - Reduced Vertical Separation Minimum
Rwy - Runway

S

S - South
SAAAR - Special Aircraft and Aircrew Authorization
Required
SAAR - Special Aircraft and Aircrew Requirements
SATNAV - Satellite Navigation
SDF - Simplified Directional Facility
SER - Start End of Runway
SFAR - Special Flight Rules Area
SFRA - Special Flight Rules Area
SFC - Surface
SIAPS - Standard Instrument Approach Procedures
SID - Standard Instrument Departure
SM - Statute Mile
SMAR - Special Military Activity Routes
SMGCS - Surface Movement Guidance and Control
System

SOIA - Simultaneous Offset Instrument Approaches
SSV - Standard Service Volume
STAR - Standard Terminal Arrival Procedure
SUA - Special Use Airspace
SVFR - Special Visual Flight Rules

W - Warning Area (Special Use Airspace)
W - West
WAAS - Wide-Area Augmentation System
WAC - World Aeronautical Chart
WP - Waypoint
WX CAM - Weather Camera (Alaska)

T

TA - Travel Advisory
TAA - Terminal Arrival Area
TAC - Terminal Area Chart
TACAN - Tactical Air Navigation
TAS - True Air Speed
TCH - Threshold Crossing Height
TDZ - Touchdown Zone
TDZE - Touchdown Zone Elevation
TERPS - U.S. Standard for Terminal Instrument Procedures
TFR - Temporary Flight Restriction
THRE - Threshold Elevation
TIBS - Telephone Information Briefing Service
TIS-B - Traffic Information Service - Broadcast
TOC - Top of Climb
TOD - Top of Descent
TODA - Takeoff Distance Available
TOGA - Takeoff/Go Around
TORA - Takeoff Runway Available
TPP - Terminal Procedures Publication
TRSA - Terminal Radar Service Area
TWEB - Transcribed Weather Broadcast
TWR - Tower

U

UC - Under Construction
UHF - Ultra High Frequency
UIR - Upper Information Region
UNICOM - Universal Communications
U.S. - United States
USAF - United States Air Force
UTA - Upper Control Area

V

VCOA - Visual Climb Over Airport / Airfield
VDA - Visual Descent Angle
VDP - Visual Decent Point
VFR - Visual Flight Rules
VGSI - Visual Glide Slope Indicator
VHF - Very High Frequency
VMC - Visual Meteorological Conditions
VNAV - Vertical Navigation
VOR - VHF Omnidirectional Radio Range
VORTAC - VHF Omnidirectional Radio Range/Tactical Air
Navigation
VPA - Vertical Path Angle
VR - Visual Route

W